

SYSTEM AND METHOD FOR CHARGING

Publication number: JP10051573 (A)

Publication date: 1998-02-20

Inventor(s): IWAMURA KEIICHI

Applicant(s): CANON KK

Classification:

- international: H04M15/12; G06F21/24; H04L12/14; H04M15/28; H04M17/02;
H04M15/10; G06F21/00; H04L12/14; H04M15/28; H04M17/00;
(IPC1-7): H04M15/12; H04L12/14; H04M15/28; H04M17/02

- European:

Application number: JP19960205951 19960805


Priority number(s): JP19960205951 19960805

Also published as:

JP3368153 (B2)

Abstract of JP 10051573 (A)

PROBLEM TO BE SOLVED: To dispense with a procedure for application to utilization or the management of data characteristic to many users and to enable charging to the provision of transmission line or terminal as well by adding the data of transmission line or terminal to pay information. SOLUTION: When the utilization request for provided information PP is generated, based on information at one part of information characteristic data PID, additional data TID of transmission line or terminal and money information PPC at least, an information utilization possibility deciding part CHECK decides whether or not the information PP can be utilized. When the decided result is acceptable, the information PP can be utilized by a user terminal.; In this case, information concerning whether or not the information PP can be utilized, information peculiar data PID, additional data TID of transmission line and terminal and memory information PPC is reported to the user terminal and displayed on a display part. The money information PPC can be cash, prepaid card or electronic information equivalent to money stored in a floppy disk, IC card or PCMCIA as well.



Data supplied from the esp@cenet database — Worldwide

[0108]an ax — a fee portioner can realize the accounting system with which needlessness, i.e., a user, and an information provider do a direct deal through a fee payment person like with the charging system shown in this embodiment. It is clear for it to be able to apply also to the electronic money which is expected that this charging system and accounting system will be put in practical use in the future and which treats a certain special data like money, or DIJ cash.

[0109]

[A 7th embodiment] Hereafter, the accounting system of a 7th embodiment concerning this invention is explained. In a 7th embodiment, about the composition of the approximately said appearance, identical codes are attached as a 1st embodiment, and the detailed explanation is omitted.

[0110]CD-ROM in which many information eniphered with the key which changes with information providers was stored. It is cheaply sold through a store, and when an information provider tells the encryption key of specification information according to the request from the user who purchased the CD-ROM, the charging system which charges the use price for the information is known. However, even if the sale profit of a medium is acquired for the store where this method sells CD-ROM, the profits to having sold the information stored in CD-ROM have the problem that it is not obtained. The above-mentioned problem is solvable by using the charging system by PPC shown by this invention also not only to use of rental information but to acquisition of information.

[0111]That is, a user also purchases PPC, such as a prepaid card, at the same time he purchases CD-ROM in a store. And when a user gets to know an encryption key by communication (a telephone etc. are included) with an information provider, the information provider can collect the use prices for information from the store which sold the prepaid card by specifying the payment by a prepaid card. Since the use price for information will also go via a store according to this method, the profits to information use can also obtain a store.

[0112]When there is the balance more than the fee of the information which is going to inspect the balance of PPC and it is going to use, a charging part decodes the code to the information, and deducts a fee from PPC. It enables it to convert the balance into money, and PPC is manufactured for every information provider, and is sold like CD-ROM through a store. Therefore, in this embodiment, the fee portioner is unnecessary.

[0113]Use information notification processing of a prepaid card can also be made safe by performing as follows use information notification processing in each embodiment mentioned above. However, the identification number iP for every prepaid card and the secret key sP corresponding to it shall be registered into the prepaid card.

[0114][Use information notification processing]

(1) If the balance of PPC is larger than the utilization charge shown in PDi when the user A wishes use of the information Pi, a charging part will permit use of the information Pi.

[0115](2) When the user A ends use of the information Pi, during use, a charging part charges the amount of money for a utilization charge directly to the balance of PPC, and writes in the result at PPC.

[0116](3) At this time, CHECK sends the notice MB of use to the information provider B. However, the amount of money charged directly to PPC is set to b.

MB = {iP, {B, b, iP, TB} sP} [0117](4) if the information provider B decodes with the secret key sP which had the message MB registered and it checks that it is right information — a fee — b — pay ** as a dividend to a store in part.

[0118]Therefore, this notice of use is ungenerable except what gets to know the identification number iP for every prepaid card, and the secret key sP corresponding to it.

[0119]

[An 8th embodiment] Hereafter, the accounting system of an 8th embodiment concerning this invention is explained. In an 8th embodiment, about the composition of the approximately said appearance, identical codes are attached as a 1st embodiment, and the detailed explanation is omitted.

[0120]In a multimedia network, since the donor of a transmission line who hits the network itself, and a quality terminal are required as shown in drawing 11 other than an information provider, it

is expected that the donor of a terminal, etc. exist. Therefore, the user needs to pay a fee not only about use of information but about use of a transmission line or a terminal. Although they may be processed by the separate fee collection system, the fee collection it is finer to charge by the information unit which it is more convenient to be processed according to one fee collection system, and is used is possible.

[0121]The charging system shown in each embodiment mentioned above is charged based on PPC which is PID and money information which an information provider sets up, and the fee collection is distributed to an information provider through a direct or fee portioner according to use. Therefore, if donors, such as a transmission line and a terminal, can add the information equivalent to PID to provided information, a fee can be correctly distributed to all the donors including an information provider with the same technique.

[0122]Drawing 12 is a figure showing the charging system which distributes a fee to all the donors about the multimedia network of an 8th embodiment by an information unit.

[0123]In drawing 12, the onerous information and PIDI (or PID) which are provided with P by the information provider and provided with PPI (or PPJ) by the information provider P are a means by which information proper data peculiar to PPI and PPC judge money information, and CHECK judges the use propriety of information. TIDI (or TIDJ) is attached data about use of the transmission line and terminal which are set up by a transmission line, the donor of a terminal, etc.

[0124]The information provider P and/or each donor begin PID to the onerous information PP, and add the data of TID etc. to it. PID and TID may use them as one data collectively. When using the information PP with a user terminal, it is constituted so that it may certainly go via a charging part, and there is a receiving window of PPC for inserting PPC on which money information was recorded in the charging part.

[0125]If the utilization request of the provided information PP arises, CHECK will judge the use propriety of the information PP based on at least a part of information on PID, TID, and PPC. For example, the utilization charge shown in PID and TID — less than the balance of PPC ***** — etc. — it is a check. If the decision result of CHECK shows C, use of the information PP by a user terminal will be attained. The information about the use propriety and PID of the information PP, TID, and PPC, including the utilization charge of the information PP, the balance of PPC, etc., is notified to a user terminal, and is displayed on an indicator. Of course, even when the utilization charge shown in PID or TID is a time basis, as long as PPC has the balance, the information PP can be used continuously. When setting up and changing a service condition by an unillustrated input part etc., a charging part deducts a predetermined fee from PPC according to the setting out and change. That is, based on time, the set-up service condition, and the fee described by PID and TID, CHECK is constituted so that a re-judging may be performed.

[0126]PPC on which the money information in this invention was recorded may be cash, may be a prepaid card like a telephone card, and may be electronic intelligence equivalent to the money stored in a floppy disk, an IC card, PCMCIA, etc.

[0127]In this invention, the use propriety of the information PP is judged by PPC which is not dependent on the user on whom money information was recorded instead of user proper data USER ID for every user. Therefore, like the embodiment mentioned above, SUBJECT (3) can be solved from SUBJECT (1) and it is **. However, in drawing 12, in order to explain simply, explanation about communication I/F was given to the abbreviation, but communication I/F can be added like other embodiments and it can also communicate with a fee portioner or a fee payment person.

[0128]According to this embodiment, TID has the same meaning as PID only by donors differing, and a user also pays the fee about TID from PPC as mentioned above. Therefore, if a fee portioner to communication distributes the fee according to use of a transmission line, a terminal, etc. to each donor directly, a just fee can be paid to all the donors about a multimedia network, and SUBJECT (4) can be solved.

[0129]Specifically, the donor of a transmission line can get justly the fee according to a circuit hour of use by describing the fee according to the circuit hour of use of the information PP to TID. If the fee corresponding to classification, such as a hour of use and a use circuit, is

described to TID, finer fee collection is also possible. The donor of a transmission line should just make the processing which adds TID to the connector etc. which connect an information provider and a network perform at this time. A connector also contains the thing all over a transmission line like a hub or a gateway. If the fee according to the hour of use and processing is similarly described to TID in the usage fee of CPU or a terminal, the donor of a terminal can get the usage fee of CPU or a terminal justly.

[0130]Below, the concrete example of the fee collection about various cases is described.
[0131]

[Example 1 of the fee collection about graphical data compression] Hierarchical encoding occurs as a coding mode for corresponding to an image processing device with different resolution, or performing image retrieval in an image database efficiently. Hereafter, the outline is explained about hierarchical encoding.

[0132]The difference information for first coding the reduction image which expresses the whole picture roughly, then expanding a reduction image one by one is coded. As a result, the scalable coding which can respond to different resolution is realizable. For example, by monitor, the reduction image with few pixel numbers is indicated by high-speed, and a printer enables it to form a detailed picture with many pixel numbers using all the information etc.

[0133]Drawing 13 is a figure showing the general concept of hierarchy code data. The header "the head of an image" indicates the beginning of the one whole picture information to be in drawing 13. The bit pattern "the header of the frame 1" indicates the beginning of the frame 1 to be, The hierarchy's 1 information that "the frame 1" coded the picture to which the original image was reduced most. The bit pattern "the header of the frame 2" indicates the beginning of the frame 2 to be, The information of the hierarchy 2 who is difference information for "the frame 2" to expand the hierarchy's 1 picture, The information of the hierarchy n who is difference information for —, the bit pattern "the header of the frame n" indicates the beginning of the frame n to be, and the "frame n" to expand the hierarchy's n-1 picture, and "the termination of an image" are information which shows the end of the one whole picture information.

[0134]As a typical hierarchy encoding system, the hierarchy encoding system (ISO/IEC10918-1,10918-2 or ITU-TT.81, T83) of JPEG, etc. are known. Such coding technology is the art in which it is well used in a multimedia network.

[0135]Below, the example which describes the fare information about the resolution by such hierarchical encoding to TID is explained.

[0136]Resolution is data which is not peculiar to the information PP. That is, even if it is the same information, according to the traffic of a transmission line, the resolution of a monitor of a user terminal, the accuracy of data retrieval, etc., the resolution by the hierarchical encoding of the information sent via a transmission line differs.

[0137]So, to TID, the fee about the resolution of hierarchical encoding in case the information PP is sent, and it, etc. are described. For example, the fees differ also using the same information PP by the case where it transmits in the hierarchy's 1 rude resolution, and the case where it transmits in the hierarchy's n precise resolution. When sending and decoding or displaying it to the hierarchy's n precise resolution, it can also be considered as the resolution to the hierarchy according to the capability of a decoder or an indicator. In this case, the fee to a whole floor layer is described by TID, and it can also be charged according to the hierarchy who used it.

[0138]Drawing 14 is a figure explaining the accounting operation in this example. The information which is provided with P by the information provider and provided with PPI (or PPj) by the information provider P in drawing 14, PIDI (or PIDj) is a means by which information proper data peculiar to PPI, the attached data which is not peculiar to the information PPI as for TIDI (or TIDj), and PPC judge money information, and CHECK judges the use propriety of the information PP.

[0139]CHECK of a charging part reads money information from PPC inserted in the receiving window of PPC, there is more the balance than the fee shown in PID and TID, and when PPC can be asked for a utilization charge, it permits use of the information PP. However, when

receiving and decoding whole floor layer data in the specified resolution, there are input parts, such as a keyboard which inputs the resolution to specify into a charging part, and the fee about TID is determined by the designated resolution. If it is less than the balance of PPC also when the fee by PID of the information PP, the fee by TID, etc. are updated by time and service conditions (use resolution etc.), it constitutes continuously so that it may be available. That is, based on the fee described by time, the service condition and PID which were set up, and TID, CHECK is constituted so that a re-judging may be performed. As other embodiments explained, magnetic cards, such as cash and a prepaid card, an IC card, etc. can be used for PPC.

[0140]When use of the information PP is permitted by CHECK, the data about the resolution described by TID with the information PP is sent to a hierarchical encoding treating part, and a hierarchical encoding treating part performs decoding processing of the hierarchy numerals corresponding to the resolution. When the information PP specifies the resolution which a user or a terminal decodes including all the hierarchy data, the resolution specified with the information PP is sent to a hierarchical encoding treating part, and a hierarchical encoding treating part performs decoding processing to the hierarchy corresponding to the specified resolution. A publicly known processing unit as shown in the hierarchy encoding system of JPEG mentioned above may be sufficient as this hierarchical encoding treating part.

[0141]Also about distribution of a fee, the same method as other embodiments can be used, therefore communication I/F can also be added to drawing 14.

[0142]The donor of a different transmission line from the information provider P, etc. develop a hierarchical encoding treating part in many cases. In this case, the donor of a transmission line provides the information provider P with a hierarchical encoding treating part with TID. The information provider P provided with TID and a hierarchical encoding treating part attaches them to the information PP together with PID, and provides for a user. If the information provider P and a network are connected by the connector etc. which are provided by the donor of a transmission line, When the information PP containing PID is sent out to a transmission line via the connector, while performing hierarchical encoding to the information PP with the connector, TID and a hierarchical encoding treating part can also be added to the information PP which performed hierarchical encoding. A connector may be in a transmission line like a hub.

[0143]When a certain organization like an information center collects and bundles up the information PP from the information provider P and provides the information PP, the information center independently, Or in collaboration with the donor of a transmission line, in addition, there is an information center, also when [which can perform hierarchical encoding to the information PP and can also set TID as it] serving both as the donor and fee portioner of a transmission line.

[0144]If a fee portioner is notified of the information about TID besides the information about PID from a user about distribution of a fee, a fee portioner will distribute the fee according to the information about notified TID to the donor of a transmission line, etc. like other embodiments. Therefore, the method described by other embodiments can be used for the structure of fee distribution. Of course, when the developer of a hierarchical encoding treating part is not a donor of a transmission line, it cannot be overemphasized that a just fee is distributed also to the developer who is a donor of a hierarchical encoding treating part.

[0145]

[Example 2 of the fee collection about graphical data compression] MPEG is known as a coding mode for accumulating and transmitting moving image information efficiently. An MPEG coding method is international standards aiming at performing high efficiency coding of video, and it performs much more high efficiency coding using the relative redundancy of a time base direction peculiar to video while it uses the frequency characteristic of moving image information, and human being's vision characteristics. MPEG1 which made the transfer rate the MPEG system with a maximum of 1.5 Mbps(es) for digital storage media, The maximum of a transmission rate is abolished and there is MPEG 2 which planned to be used by all the transmission systems of bidirectional digital multimedia apparatus, a digital video tape recorder, ATV (AdvancedTV), an optical fiber network, etc. Since the fundamental algorithm of MPEG1 and MPEG 2 is almost the same, the principle and data structure of the coding mode are explained

by using MPEG1 as a base.

[0146]First, the principle of the low bit rate coding method by MPEG is explained. In an MPEG system, the relative redundancy of a time base direction is dropped on taking inter-frame difference, and DCT and the thing for which variable-length-coding processing is carried out and the relative redundancy of the direction of space is dropped realize high efficiency coding for the difference data obtained by this as a whole. In the case of an animation, about the relative redundancy of a time base direction, it becomes possible to drop relative redundancy by taking in time difference with precedence or the frame which carries out backward with the frame which correlation of the continuous frame tends to code paying attention to a high thing.

[0147]Then, besides the intra coding picture (I-picture) acquired in MPEG in the mode chiefly coded within a frame as shown in drawing 15, The difference value of the forward prediction coded image (P-picture) which codes a difference value with the frame preceded in time, and the frame preceded in time or the frame which carries out backward, Or it had a both-directions prediction-coding picture (B-picture) which codes what has the fewest data volume among difference values with the interpolation frame from these frames, and each frame by such coding modes is combined in the given order.

[0148]In MPEG, I-picture mentioned above, P-picture, and B-picture are made into one unit (GOP) by one sheet, four sheets, and ten sheets, respectively, and I-picture is allotted to a head, then the combination which repeats and arranges B-picture of two sheets and P-picture of one sheet is recommended. While making possible reverse direction reproduction of an animation, and partial regeneration which makes GOP a unit by arranging I-picture with a constant period, prevention of error propagation is aimed at. When a new object appears in a frame, the direction of the difference value which took difference with the frame which carries out backward may decrease rather than taking difference with the frame preceded in time. So, in MPEG, the above both-directions prediction coding is performed and more highly efficient coding is performed.

[0149]A motion compensation is performed in MPEG. An 8x8-pixel block about luminance data Namely, 4 blocks, In the prescribed block (macro block) unit collected 2 blocks about color difference data. Difference with the macro block near the corresponding block of precedence or a backward frame is taken, by searching for a macro block with few differences, a motion vector is detected and this motion vector is coded as data. In the case of decoding, the correspondence macro block data of precedence or a backward frame are extracted using this motion vector, and it decodes the code data coded using the motion compensation by this. Once coding the frame preceded in time on the occasion of such a motion compensation, the decoded frame is obtained again, it is considered as a precedence frame, and a motion compensation is performed using the macro block in this frame, and the macro block of the frame which it is going to code. Although MPEG1 performs an inter-frame motion compensation, MPEG 2 performs the motion compensation between the fields. High efficiency coding of the difference data and the motion vector which were obtained by such motion compensation is further carried out by DCT and Huffman encoding which were explained previously.

[0150]Next, the structure of this MPEG data is explained. MPEG data comprises a layered structure which consists of a video sequence layer, a GOP layer, a picture layer, a slice layer, a macro block layer, and a block layer. Hereafter, it explains sequentially from a lower layer.

[0151]First, a block layer comprises 8x8 pixels for every luminance data and color difference data like previous JPEG, respectively, and DCT is performed for every unit of this.

[0152]Luminance data is summarized into 4 blocks and a macro block layer packs each into 1 block the 8x8-pixel block mentioned above about color difference data, is what attached the macro block header, and makes it the motion compensation which mentions this macro block later, and the unit of coding in an MPEG system. A macro block header contains each data of the motion compensation of each macro block unit, and a quantization step, and the data of being that six DCT blocks (Y0, Y1, Y2, Y3, Cr, Cb) in each macro block have data.

[0153]A slice layer comprises one or more the macro blocks and slice headers which stand in a row in the scanning order of a picture, and can set constant the quantization step in a series of macro blocks in the same slice layer. A slice header sets constant the quantization step in the

slice layer, when it has data about the quantization step in each slice layer and there are no quantization step data peculiar to each macro block. A top macro block resets the difference value of a dc component.

[0154]A picture layer collects two or more slice layers per frame, and comprises a header which consists of picture start codes etc., and one or more slice layers following this. The code (coding identification signal) which shows the coding mode of a picture, and the code which shows the accuracy (are they a pixel unit or a half a pixel unit?) of motion detection are contained in a header.

[0155]A GOP layer comprises a header containing a group start code, the time code which shows the time from the beginning of a sequence, etc., and two or more I frames, B frames or p frames following this.

[0156]It begins from a sequence start code, and ends by a sequence end code, and a video sequence layer is arranged by two or more GOP(s) with same control data, image size, etc. required for decoding of image size, an aspect ratio, etc. between them.

[0157]As for the bit stream, the MPEG system with the above data structures is specified. Such coding technology is the art in which it is well used in a multimedia network.

[0158]Below, the picture data by such MPEG explain the example described by TID.

[0159]Picture data are data which is not peculiar to the information PP. That is, even if it is the same information, the encoding efficiency of MPEG demanded according to the traffic of a transmission line, the resolution of a monitor of a user, etc. differs. So, the fee about the information about the picture of MPEG in case the information PP is sent, and it, etc. shall be described by TID. For example, the fees described by TID differ at the fee to transmission of the top delivery video which lessened transmission of P-picture or B-picture also for the same information, and the fee to transmission of the video using all the pictures. When transmitting all the pictures and decoding or displaying it, decoding by the picture specified according to the capability of a decoder or an indicator can also be performed. In this case, the fee to all the pictures will be shown in TID, and it will be charged at it according to the used picture.

[0160]Drawing 16 is a figure explaining the accounting operation in this example. The information which is provided with P by the information provider and provided with PPI (or PPj) by the information provider P in drawing 16, PIDI (or PIDj) is a means by which information proper data peculiar to the information PPI, the attached data which is not peculiar to the information PPI as for TIDI (or TIDj), and PPC judge money information, and CHECK judges the use propriety of the information PP.

[0161]A user inserts PPC in the receiving window of PPC. CHECK of a charging part reads money information from PPC, there is more balance of PPC than the fee shown in PID and TID, and when PPC can be asked for a utilization charge, it permits use of the information PP. However, when all the pictures are transmitted and it decodes by a specification picture, there is an input part which is not illustrated [of the keyboard etc. which input into a charging part the information which shows a specification picture], and the fee about TID is judged by it. Also when a time basis or service conditions (use resolution etc.) change the utilization charge by PID of the information PP, and the utilization charge by TID, as long as PPC has the balance, the information PP can be used continuously. That is, based on the balance of the fee described by time, the set-up service condition, PID, and TID and PPC, CHECK is constituted so that a re-judging may be performed. As other embodiments explained, magnetic cards, such as cash and a prepaid card, an IC card, etc. may be sufficient as PPC.

[0162]When use of the information PP is permitted by CHECK, the data about the picture described with the information PP at TID is sent to an MPEG processing part, and an MPEG processing part performs decoding processing corresponding to the picture. Also when the picture which the information PP decodes from a user or a terminal including all the pictures is specified, the specification information is sent to an MPEG processing part with the information PP, and an MPEG processing part performs decoding processing corresponding to a specification picture. This MPEG processing part is a publicly known processing unit.

[0163]About distribution of a fee, the same method as other embodiments can be used. Therefore, communication I/F can also be added to the composition shown in drawing 16.

[0164]The donor of a different transmission line from the information provider P, etc. develop a hierarchical encoding treating part in many cases. In this case, the donor of a transmission line provides the information provider P with a hierarchical encoding treating part with TID. The information provider P provided with TID and a hierarchical encoding treating part attaches them to the information PP together with PID, and provides for a user. If the information provider P and a network are connected by the connector etc. which are provided by the donor of a transmission line, When the information PP containing PID is sent out to a transmission line via the connector, while performing hierarchical encoding to the information PP with the connector, TID and a hierarchical encoding treating part can also be added to the information PP which performed hierarchical encoding. A connector may be in a transmission line like a hub.

[0165]When a certain organization like an information center collects and bundles up the information PP from the information provider P and provides the information PP, independently, in collaboration with the donor of a transmission line, the information center can perform hierarchical encoding to the information PP, and can also set TID as it. An information center may serve both as the donor and fee portioner of a transmission line.

[0166]If a fee portioner is notified of the information about TID besides the information about PID from a user about distribution of a fee, a fee portioner will distribute the fee according to the information about notified TID to the donor of a transmission line, etc. like other embodiments. Therefore, the method described by other embodiments can be used for the structure of fee distribution. Of course, when the developer of a hierarchical encoding treating part is not a donor of a transmission line, it cannot be overemphasized that a just fee is distributed also to the developer who is a donor of a hierarchical encoding treating part.

[0167]In this example, although MPEG was taken up as an example of coding, all the methods of charging using PPC are contained in this embodiment about the coding using the difference on a time-axis.

[0168]

[The example about the fee collection of encoding technology] Below, the fee collection to the encoding technology for not making it use in addition to the user who specified the information provided is explained.

[0169]In order that a multimedia network may deal with various information, the processing speed and the safety which are demanded according to the kind of information differ from each other greatly. For example, when it is data as which high-speed real time nature is required with large scale like video, When it is data in which high-speed cipher processing is required and real time nature is not demanded with the small capacity represented by a document and software, to make cipher-processing speed late and to reduce the load about cipher processing is desired. Cipher processing with low safety about scramble may be sufficient as data like video in many cases, and, in the case of a document or data like software, cipher processing with high safety is desired in many cases. Therefore, the fee collection corresponding to the processing speed and the safety which are demanded is wanted to realize.

[0170]Below, the fee to the processing speed and intensity of a code explains the example described by TID.

[0171]Drawing 17 is a figure explaining the accounting operation in this example. The information which is provided with P by the information provider and provided with PPI (or PPJ) by the information provider P in drawing 17, PIDI (or PIDj) is a means by which information proper data peculiar to the information PPI, the attached data which is not peculiar to the information PPI as for TIDI (or TIDj), and PPC judge money information, and CHECK judges the use propriety of the information PP.

[0172]A user inserts PPC in the receiving window of PPC. CHECK of a charging part reads money information from PPC, there is more balance of PPC than the fee shown in PID and TID, and when PPC can be asked for a utilization charge, it permits use of the information PP. However, when all the pictures are transmitted and it decodes by a specification picture, there is an input part which is not illustrated [of the keyboard etc. which input into a charging part the information which shows a specification picture], and the fee about TID is judged by it. Also when the utilization charge by PID of the information PP and the utilization charge by TID

change according to a time basis or service conditions (processing speed, intensity, etc. of a code), as long as PPC has the balance, the information PP can be used continuously. That is, based on the balance of the fee described by time, the set-up service condition, PID, and TID and PPC, CHECK is constituted so that a re-judging may be performed. As other embodiments explained, magnetic cards, such as cash and a prepaid card, an IC card, etc. may be sufficient as PPC.

[0173]When use of the information PP is permitted by CHECK, the data about the processing speed and intensity of a code which were described with the information PP at TID is sent to a cipher-processing part, and a cipher-processing part performs cipher processing corresponding to the processing speed and intensity. The composition of the cipher-processing part which performs cipher processing according to different processing speed and intensity is explained in full detail by Japanese Patent Application No. No. 165187 [seven to] for which these people applied previously.

[0174]About distribution of a fee, the same method as other embodiments can be used. Therefore, communication I/F can also be added to the composition shown in drawing 17.

[0175]The donor of a different transmission line from the information provider P, etc. develop a cipher-processing part in many cases. In this case, the donor of a transmission line provides the information provider P with a cipher-processing part with TID. The information provider P provided with TID and a cipher-processing part attaches them to the information PP together with PID, and provides for a user. If the information provider P and a network are connected by the connector etc. which are provided by the donor of a transmission line, When the information PP containing PID is sent out to a transmission line via the connector, while performing cipher processing to the information PP with the connector, TID and a cipher-processing part can also be added to the enciphered information PP. A connector may be in a transmission line like a hub.

[0176]When a certain organization like an information center collects and bundles up the information PP from the information provider P and provides the information PP, the information center independently, Or in collaboration with the donor of a transmission line, in addition, there is an information center, also when [which can encipher to the information PP and can also set up TID] serving both as the donor and fee portioner of a transmission line.

[0177]If a fee portioner is notified of the information about TID besides the information about PID from a user about distribution of a fee, a fee portioner will distribute the fee according to the information about notified TID to the donor of a transmission line, etc. like other embodiments. Therefore, the method described by other embodiments can be used for the structure of fee distribution. Of course, when the developer of a cipher-processing part is not a donor of a transmission line, it cannot be overemphasized that a just fee is distributed also to the developer who is a donor of a cipher-processing part.

[0178]Although Japanese Patent Application No. No. 165187 [seven to] for which these people applied previously as a cipher-processing part was taken up in this example, What is necessary is just a cipher-processing part which performs cipher processing according to different processing speed and intensity, and all the methods of charging according to the processing speed and intensity of a code are contained in this embodiment using PPC.

[0179]

[The example of the fee collection according to the kind of code] Although the aforementioned example explained how to charge according to the processing speed and intensity of a code, as shown in drawing 18, in the case of the network with which not only the processing speed and intensity of a code but the kinds (RSA, FEAL, DES, ...) of code differ, it is important to realize fee collection according to the kind of code. In this case, if the fee according to the kind of code to be used is described by TID, it is clear by collecting the fee according to it from PPC that the fee collection according to various codes is realizable. However, the information PP shall be enciphered in the code described at TID.

[0180]Fine setting out according to the processing speed and intensity of the code may be described by TID about each code like the aforementioned example. In this case, it is clear for it to be able to realize like the aforementioned example by composition shown in drawing 17.

However, the cipher-processing part shown in drawing 17 is a cipher-processing part with which each user terminal is provided.

[0181]The fee collection corresponding to the case where each user terminal can choose the code to be used according to the kind of information PP is also considered. The cipher-processing part which can choose such a code to be used is shown in Japanese Patent Application No. No. 165392 [seven to] for which these people applied previously. Therefore, if the cipher-processing part shown in drawing 17 is made into the cipher-processing part shown in Japanese Patent Application No. No. 165392 [seven to], the fee collection corresponding to the case where a code is chosen by the same composition as drawing 17 is also realizable. At this time, the kind of all the codes and the fee corresponding to it are described by TID, and fee collection based on TID is performed to it according to the used code. Of course, fine setting out about fee collection can also be described to TID for every code.

[0182]

[The example of the fee collection to image quality] This example is charged to the image quality of the information PP. Image quality is dynamic ranges, gradation, etc. of a measure, such as a frame number per unit time, a pixel number, a chromaticity of each pixel, chroma saturation, and brightness. Image quality becomes high, so that each item has a larger dynamic range and finer gradation. Below, the example which describes each item of image quality to TID is explained.

[0183]These items that show image quality are data which is not peculiar to information. That is, even if it is the same information, according to the traffic of a transmission line, the resolution of a monitor of a user terminal, the accuracy of data retrieval, etc., the image quality of the information sent via a transmission line differs.

[0184]So, to TID, the fee about image quality in case the information PP is sent, and it, etc. are described. For example, the fees differ by the case where the information that resolution is rude is transmitted also for the same information PP, and the case where the information that resolution is fine is transmitted. It can send by the highest image quality and the picture of image quality as occasion demands can also be displayed. In this case, the fee to all the image quality is described by TID, and it can also be charged according to the used image quality.

[0185]Drawing 19 is a figure explaining the accounting operation in this example. The information which is provided with P by the information provider and provided with PPi (or PPj) by the information provider P in drawing 19, PIdi (or PIDj) is a means by which information proper data peculiar to PPi, the attached data which is not peculiar to the information PPi as for TIDi (or TIDj), and PPC judge money information, and CHECK judges the use propriety of the information PP.

[0186]CHECK of a charging part reads money information from PPC inserted in the receiving window of PPC, there is more the balance than the fee shown in PId and TID, and when PPC can be asked for a utilization charge, it permits use of the information PP. However, when the data of all the image quality is transmitted and it displays by the appointed image quality, there is an input part which is not illustrated [of the keyboard etc. which input into a charging part the information which shows specification image quality], and the fee about TID is judged by it. Also when a time basis or service conditions (image quality etc.) change the utilization charge by PId of the information PP, and the utilization charge by TID, as long as PPC has the balance, the information PP can be used continuously. That is, based on the balance of the fee described by time, the set-up service condition, PId, and TID and PPC, CHECK is constituted so that a re-judging may be performed. As other embodiments explained, magnetic cards, such as cash and a prepaid card, an IC card, etc. may be sufficient as PPC.

[0187]When use of the information PP is permitted by CHECK, the data about the image quality described with the information PP at TID is sent to a picture display part, and a picture display part displays the picture of the image quality. Also when the image quality which the information PP displays from a user or a terminal including the data of all the image quality is specified, the specification information is sent to a picture display part with the information PP, and a picture display part displays the picture of specification image quality.

[0188>About distribution of a fee, the same method as other embodiments can be used.

Therefore, communication I/F can also be added to the composition shown in drawing 19.

[0189]The donor of a different transmission line from the information provider P, etc. develop a picture display part in many cases. In this case, the donor of a transmission line provides the information provider P with a picture display part with TID. The information provider P provided with TID and a picture display part attaches them to the information PP together with PID, and provides for a user. If the information provider P and a network are connected by the connector etc. which are provided by the donor of a transmission line, when the information PP containing PID will be sent out to a transmission line via the connector, TID and a picture display part can also be added to the information PP with the connector. A connector may be in a transmission line like a hub.

[0190]When a certain organization like an information center collects and bundles up the information PP from the information provider P and provides the information PP, the information center can also set a picture display part and TID as the information PP in collaboration with the donor of a transmission line independently. An information center may serve both as the donor and fee portioner of a transmission line.

[0191]If a fee portioner is notified of the information about TID besides the information about PID from a user about distribution of a fee, a fee portioner will distribute the fee according to the information about notified TID to the donor of a transmission line, etc. like other embodiments. Therefore, the method described by other embodiments can be used for the structure of fee distribution. Of course, when the developer of a hierarchical encoding treating part is not a donor of a transmission line, it cannot be overemphasized that a just fee is distributed also to the developer who is a donor of a hierarchical encoding treating part.

[0192]The example mentioned above explained how to charge about a circuit, a user terminal, graphical data compression, a code, image quality, etc. The charging system concerning this invention can apply also describing the object charged at TID etc. by specifying the form of TID also to the network with which a circuit, a user terminal, graphical data compression, a code, image quality, etc. are intermingled.

[0193]By specifying the form of describing the kind of processing to PID or TID, the charging method of this invention. It is clear that it is applicable to the various processes other than the processing mentioned above, and the donor of be [it / a high charging method of the pliability which can enter freely] who provides various information about networks other than the information provider who mentioned above is also clear.

[0194]The fee collection applicable to the processing speed in processing of versatility, such as not only a code but image coding, according to the processing speed of the code of the example mentioned above is clear. Safety and not only the intensity of a code but applicable to various safeties, such as access control, are clear.

[0195]Even if it does not exchange TID with the information PP, it exchanges independently as data of a specific form, and as long as the fee shown in TID becomes below in the balance of PPC, after transmitting the information PP, fee collection about PID may be performed to use of the information PP.

[0196]As shown in drawing 20, PID as well as TID may be independently exchanged as data of a specific form. In this case, if the information PP is transmitted only when the fee about PID and TID is less than the balance of PPC, a transmission line can be used efficiently.

[0197]Even if the TID passes a network as mentioned above and it is not carried out when TID is data peculiar to a user terminal as shown in drawing 21 for example, If the data about stored TID is checked when the user terminal has a storage of TID and CHECK judges the propriety of use of the information PP, it is also clear that same accounting can be performed. Since TID is not data peculiar to the information PP, this [its] is effective not only to a user terminal but a portion peculiar to TID.

[0198]It is contained in zero (no charge), that is, a fee. Therefore, a part can also use [the information PP or] some them for free (low resolution picture in hierarchical encoding, etc.).

[0199]

[A 9th embodiment] Hereafter, the accounting system of a 9th embodiment concerning this invention is explained. In a 9th embodiment, about the composition of the approximately said appearance, identical codes are attached as a 1st embodiment, and the detailed explanation is

37

【0250】また、利用者以外にも、スポンサが料金を負担することができる。種々の用途に対応する課金システムを実現することもできる。

【0251】さらに、時間や使用条件の段階に応じて情報の利用可否を判定したり、課金条件を変えるなどが可能であり、きめ細かな課金システムを実現することができる。

【0252】

【発明の効果】以上説明したように、本発明によれば、利用申し込み手続、多数の利用者固有データの管理が不要な課金システムおよびその方法を提供することができる。

【0253】また、利用者のプライバシーを保護する課金システムおよびその方法を提供することができる。

【0254】また、料金の請求および徴収が容易な課金システムおよびその方法を提供することができる。

【0255】また、提供情報だけでなく伝送路や端末の提供に対する課金も行う課金システムおよびその方法を提供することができる。

【0256】また、提供情報の利用の段階に応じて利用可否を判定し、その判定結果に応じて情報の利用を制限し、課金を行う課金システムおよびその方法を提供することができる。

【図面の簡単な説明】

【図1】 超流通の概念図、

【図2】 第1実施形態の課金方式を示す図、

【図3】 第2実施形態の課金方式を示す図、

【図4】 第3実施形態の課金方式を示す図、


【図5】 第3実施形態におけるネットワークを示す図、

【図6】 第4実施形態の課金方式を示す図、

【図7】 第4実施形態におけるネットワークを示す図、

【図8】 第5実施形態の課金方式を示す図、

【図1】



(28)

特開平10-51573

38

* 【図9】 第6実施形態の課金方式を示す図、

【図10】 第6実施形態におけるネットワークを示す図、

【図11】 第8実施形態におけるネットワークを示す図、

【図12】 第8実施形態のマルチメディアネットワークに関するすべての提供者へ情報単位で料金を分配する課金方式を示す図、

【図13】 階層符号データの一般的な概念を示す図、

【図14】 画像圧縮に関する課金の実施例1における課金動作を説明する図、

【図15】 MPEGにおけるI、P、B-ピクチャの組み合わせを示す図、

【図16】 画像圧縮に関する課金の実施例2における課金動作を説明する図、

【図17】 暗号技術の課金に関する実施例における課金動作を説明する図、

【図18】 暗号の種類に応じた課金の実施例における課金動作を説明する図、

【図19】 画像品位に対する課金の実施例における課金動作を説明する図、

【図20】 第8実施形態における第二の課金方式を示す図、


【図21】 第8実施形態における第三の課金方式を示す図、

【図22】 第9実施形態におけるネットワークを示す図、

【図23】 第9実施形態における課金動作を説明する図、

【図24】 第10実施形態における課金動作を説明する図である。

【図2】 FIG. 2



(22)

[図9]




FIG. 12

[図12]




FIG. 14

[図14]






FIG. 11

[図11]



[図13] FIG. 13



[図15] FIG. 15





FIG. 16

[図16]



【圖 18】






FIG. 20



【图 2 2】



(19) 日本国特許庁 (J P)

(12) 公開特許公報 (A)

(11) 特許出願公開番号

特開平10-51573

(43) 公開日 平成10年(1998) 2月20日

(51) Int.Cl. [*]	識別記号	序内整理番号	F I	技術表示箇所
H 0 4 M 15/12			H 0 4 M 15/12	
H 0 4 L 12/14			15/28	C
H 0 4 M 15/28			17/02	A
17/02		9744-5K	H 0 4 L 11/02	F

審査請求 未請求 請求項の数21 O L (全 24 頁)

(21) 出願番号 特願平8-205951

(22) 出願日 平成 8 年(1996) 8 月 5 日

(71) 出願人 000001007

キヤノン株式会社

東京都大田区下丸子 3 丁目30番 2 号

(72) 発明者 岩村 恵市

東京都大田区下丸子 3 丁目30番 2 号 キヤ

ノン株式会社内


(74) 代理人 弁理士 大塚 康徳 (外 1 名)

(54) 【発明の名称】 課金システムおよびその方法

(57) 【要約】

【課題】 超流通においては、情報の利用が許可された利用者であるかどうかを判定するための利用者に固有のデータが必要になり、利用申し込み手続や、多数の利用者の固有データの管理が煩雑である。

【解決手段】 マルチメディアネットワークを介して、マルチメディア情報と、そのマルチメディア情報に固有の課金情報とを受信し、受信した課金情報および金銭情報が記録された媒体の金銭情報に基づき、受信したマルチメディア情報の利用可否を判定する。



【特許請求の範囲】

【請求項1】 マルチメディアネットワークを介した情報の提供に課金するための課金システムであって、前記マルチメディアネットワークを介して、マルチメディア情報と、そのマルチメディア情報に固有の第一の課金情報とを受信する受信手段と、金銭情報が記録された媒体の金銭情報を操作する操作手段と、前記第一の課金情報および前記金銭情報に基づき、前記受信手段により受信されたマルチメディア情報の利用可否を判定する判定手段とを備えることを特徴とする課金システム。

【請求項2】 前記受信手段は、さらに、前記マルチメディア情報に固有ではない第二の課金情報を受信し、前記判定手段は、前記第一および第二の課金情報と前記金銭情報とに基づき、前記受信手段により受信されたマルチメディア情報の利用可否を判定することを特徴とする請求項1に記載された課金システム。

【請求項3】 前記受信手段は、さらに、前記マルチメディア情報に付加された付加情報に関する第三の課金情報を受信し、前記判定手段は、前記第一から第三の課金情報と前記金銭情報とに基づき、前記受信手段により受信されたマルチメディア情報の利用可否を判定することを特徴とする請求項に記載された課金システム。

【請求項4】 前記判定手段は、前記マルチメディア情報の利用可否を段階的に判定することを特徴とする請求項1から請求項3の何れかに記載された課金システム。

【請求項5】 さらに、前記マルチメディア情報および/または前記付加情報の利用履歴を記憶する記憶手段を備え、

前記判定手段は、前記記憶手段から読出した利用履歴に対応する前記第一から第三の課金情報の少なくとも一つと、前記金銭情報とに基づき、前記受信手段により受信されたマルチメディア情報の利用可否を判定することを特徴とする請求項3または請求項4の何れかに記載された課金システム。

【請求項6】 前記操作手段は、前記判定手段による判定に基づき、前記媒体の金銭情報を操作することを特徴とする請求項1から請求項5の何れかに記載された課金システム。

【請求項7】 前記金銭情報が記録された媒体はプリペイドカードであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項8】 前記金銭情報は、前記媒体に磁気的または電子的に記録された情報であることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項9】 前記第一および/または第二の課金情報に応じた金銭情報が記録された前記媒体を用いることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項10】 前記操作手段は、前記ネットワークを介して前記金銭情報および/または前記マルチメディア情報の利用情報を入力出力することを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項11】 前記操作手段から前記マルチメディア情報の利用情報を受信した料金分配者は、その利用情報に見合う料金を前記マルチメディア情報の提供者に分配することを特徴とする請求項10に記載された課金システム。

【請求項12】 前記第二の課金情報は通信回線の使用に関するものであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項13】 前記第二の課金情報は端末の使用に関するものであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項14】 前記第二の課金情報は画像の解像度に関するものであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項15】 前記第二の課金情報はMPEGのピクチャに関するものであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項16】 前記第二の課金情報は情報の安全性に関するものであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項17】 前記第二の課金情報は符号の処理速度に関するものであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項18】 前記第二の課金情報は符号の種類に関するものであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項19】 前記第二の課金情報は画像品位に関するものであることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項20】 前記記憶手段に記憶される利用履歴には、前記マルチメディア情報の最終利用を示す情報が含まれることを特徴とする請求項1から請求項6の何れかに記載された課金システム。

【請求項21】 マルチメディアネットワークを介した情報の提供に課金するための課金方法であって、

前記マルチメディアネットワークを介して、マルチメディア情報と、そのマルチメディア情報に固有の第一の課金情報とを受信する受信ステップと、金銭情報が記録された媒体の金銭情報を操作する操作ステップと、

前記第一の課金情報および前記金銭情報に基づき、前記受信ステップで受信したマルチメディア情報の利用可否を判定する判定ステップとを備えることを特徴とする課金方法。

【発明の詳細な説明】

【0001】

【発明の属する技術分野】本発明は課金システムおよびその方法に関し、例えば、動画像、静止画像、サウンド、コンピュータプログラム、その他データを含む情報を伝送し提供するマルチメディアネットワークにおける課金システムおよびその方法に関するものである。

【0002】

【従来の技術】近年、幹線通信網における光ファイバネットワークの整備、ケーブルテレビシステムの普及、衛星通信の実用化、ローカルエリアネットワークの普及などが急速に進んでいる。さらに、これらの通信網の相互接続も積極的になされている。これらの通信網を用いて、キャラクターデータ、静止画、サウンド、動画などを含む所謂マルチメディア情報が世界的な規模で交換されるようになった。

【0003】これに伴い、かかる通信網を利用して様々な情報を提供し、その情報の内容および量に応じて料金を徴収する、所謂情報サービス産業が増大している。このようなサービスにおいては、提供した情報に対する課金を適切に行うことが重要である。さらに、デジタルデータであるマルチメディア情報は、編集や変形といった情報の変更が容易であり、情報の配布や売買といった流通だけでなく、提供情報の変更についても適切に課金をすることができざる技術が必要になる。

【0004】また、情報の保護は不完全であり、プログラムやサウンドを含む映像情報の不正利用が問題になっている。情報の不正利用を防ぐために、コピー防止機能が付けたり、コンピュータなどに付与されているハードウェア機番に相当する番号をソフトウェアにも付与して、ソフトウェアの実行時に、二つの番号を照合する、などの方法がある。しかし、コピー防止機能は、ソフトウェアをバックアップする際などに不便だし、番号を照合する方法は、番号の管理や販売に関して不便であり、あまり実用的ではない。

【0005】それに対して、「超流通」というソフトウェア権利者(以後「情報提供者」という)の権利保護を目指した概念が森永一氏によって提案され、特開昭60-77218、特開昭60-191322、特開昭64-68835、特開平2-44447、特開平4-64129などに示されている。

【0006】図1は特開平4-64129に示された超流通の概念図である。情報提供者Pは、提供するソフトウェアPP1(またはPPj)の利用可否を、ソフトウェアに固有のデータPID1(またはPIDj)と、利用者のUSER-IDとの条件によってCHECKで判定し、利用可ならばソフトウェアの利用履歴をSHに記録する。そして、情報提供者Pは、履歴に基づきソフトウェアの利用料金を請求する。なお、図に示すSSUは、以上の各手段を含むソフトウェアサービスユニットである。

【0007】

【発明が解決しようとする課題】しかし、上述した技術においては、次のような問題点がある。

【0008】(1)超流通は、情報提供者に情報の利用が許可された利用者であるかどうかを利用者に固有のデータによって判定する。そのため、超流通の実現手段は、少なくとも利用者に固有のデータを格納する格納手段を有する。従って、情報を利用しようとする者は、予め情報提供者に情報の利用を申し込み、USER-IDを得、利用者固有データとして登録する必要がある。利用申し込み手続や、多数の利用者固有データ(USER-ID)の管理は煩雑である。

10 【0009】(2)情報の不正利用を防止するため、または、提供する情報の利用状況を情報提供者が把握するために、超流通の実現手段は、情報の利用履歴を格納する格納手段を備えている。情報提供者は、この履歴に基づいて利用者に料金を請求する。超流通においては、情報は買い取りではなくレンタル的な扱いをするため、利用履歴が必要になる。しかし、利用者がどのような情報を利用したかという利用履歴は利用者のプライバシーに関わり、利用者のプライバシーをどのように保護するかという課題がある。

20 【0010】(3)超流通は、提供情報の利用状態を正しく把握する、すなわち料金を正しく課するための手段および方式であるが、料金の支払いに関する手段や方式を含んでいない。従って、情報提供者は超流通以外の手段により料金の請求および徴収を行う必要がある。

【0011】(4)超流通によるソフトウェアに固有のデータを付いた課金は、情報量は小さいが、それを利用することによって価値があるコンピュータプログラムなどの情報を目的にするものである。リアルタイムの動画像などのように情報量が非常に大きい情報の提供においては、その利用料金だけでなく、伝送に対する料金も大きくなる。しかし、超流通は、回線使用料やマルチメディア端末の使用料などに関する課金には対応していない。提供情報だけでなく伝送路や端末の提供に対する課金もえらる方式が望まれる。

30 【0012】(5)超流通は、提供する情報の利用可否を判定するが、判定後の利用に関しては何の制限ももない。利用の段階に応じて利用可否を判定し、その判定結果に応じて情報の利用を制限することができる方式が望まれる。

40 【0013】本発明は、上述した問題を個々に、または、まとめて解決するためのものであり、利用申し込み手続や、多数の利用者固有データの管理が不要な課金システムおよびその方法を提供することを目的とする。

【0014】また、利用者のプライバシーを保護することができざる課金システムおよびその方法を提供することを他の目的とする。

【0015】また、料金の請求および徴収が容易な課金システムおよびその方法を提供することを他の目的とする。

50 【0016】また、提供情報だけでなく伝送路や端末の

提供に対する課金も行うことができる課金システムおよびその方法を提供することを他の目的とする。

【0017】また、提供情報の利用の段階に応じて利用可否を判定し、その判定結果に応じて情報の利用を制限し、課金を行うことができる課金システムおよびその方法を提供することを他の目的とする。

【0018】

【課題を解決するための手段】本発明は、前記の目的を達成する一手段として、以下の構成を備える。

【0019】本発明にかかる課金システムは、マルチメディアネットワークを介した情報の提供に課金するための課金システムであって、前記マルチメディアネットワークを介して、マルチメディア情報と、そのマルチメディア情報に固有の第一の課金情報とを受信する受信手段と、金銭情報が記録された媒体の金銭情報を操作する操作手段と、前記第一の課金情報および前記金銭情報に基づき、前記受信手段により受信されたマルチメディア情報の利用可否を判定する判定手段とを有することを特徴とする。

【0020】また、本発明にかかる課金方法は、マルチメディアネットワークを介した情報の提供に課金するための課金方法であって、前記マルチメディアネットワークを介して、マルチメディア情報と、そのマルチメディア情報に固有の第一の課金情報とを受信する受信ステップと、金銭情報が記録された媒体の金銭情報を操作する操作ステップと、前記第一の課金情報および前記金銭情報に基づき、前記受信ステップで受信したマルチメディア情報の利用可否を判定する判定ステップとを有することを特徴とする。

【0021】

【発明の実施の形態】以下、本発明にかかる一実施形態の課金システムを図面を参照して詳細に説明する。

【0022】

【第1実施形態】図2は本発明にかかる第1実施形態の課金方式を示す図である。図2において、Pは情報提供者、PP1（またはPPj）はPによって提供される有償の情報、PIDi（またはPIDj）はPP1に固有の情報固有データ、PPCは金銭情報、CHECKは利用可否の判定データである。

【0023】情報提供者Pは、PIDを含めた形で情報PPを提供する。情報PPは、パーソナルコンピュータなどの利用者端末において利用される際、必ず課金部を経由するように構成しており、その課金部には金銭情報であるPPCの受け口がある。

【0024】情報PPの利用要求が生じると、利用可否判定部CHECKは、PIDおよびPPCの少なくとも一部の情報に基づいて、情報PPの利用の可否をチェックし、判定結果を利用者端末に通知する。例えば、CHECKは、PIDに示された利用料金とPPCの金銭情報とを照合するか否かなどのチェックを行う。もし、CHECKの判定結果がOKであれば、利用者端末において情報PPの利用が可能になる。こ

のときのPIDやPPCに関する情報、つまりPPの利用料金やPPCの残高などは、表示部に表示される。また、CHECKによる判定結果も表示部に表示することができる。

【0025】PPCには、現金、プリペイドカードなどが利用できるが、記憶媒体（フロッピーディスク、磁気カード、ICカード、PCMCIAカードなど）に格納された金銭と等価な電子の情報、所謂ディジタリゼーションや電子マネーと呼ばれるものであってもよい。

【0026】すなわち、本実施形態においては、利用者ごとの固有データUSER-IDを用いる代わりに、利用者に依存しない金銭情報PPCによって情報PPの利用可否を判定する。従って、利用者は、USER-IDなどを得るための申込手続をする必要がなく、実際の金銭、または金銭と等価な金銭情報PPCをもつだけでよい。つまり、利用者は、利用する情報PPの利用料を支払うだけである。また、多数の利用者固有データを管理する必要がなく、前述した課題(1)を解決することができる。

【0027】また、本実施形態においては、利用者固有データを必要としないため、情報提供者Pは、どの利用者が情報PPを利用したかを知ることができない。しかし、情報提供者Pは、情報PPの利用に応じた料金が支払われさえすれば充分であり、どの利用者が情報PPを利用したかという利用者のプライバシーに関わる情報を知る必要はない。従って、前述した課題(2)を解決することができる。

【0028】従って、本実施形態においては、どのUSER-IDをもつ利用者が、どの情報PPを利用したかという利用履歴を格納する格納部をもたないが、どの情報PPが何度利用されたかという利用頻度を格納する格納部、または、情報PPを現在利用していることを知らせる利用通知部を有することはできる。図2においては、点線で示す経路により、利用通知が情報提供者Pに送られる。具体的な利用頻度格納部または利用通知部は後述する実施形態で詳細に説明する。

【0029】本実施形態においては、PPCは金銭と等価な情報であるので、PPCを用いることと自分が料金の支払いに相当する。これにより、前述した課題(3)も解決されるが、具体的なPPCの入手法と回収法、および料金の分配法は、課題(2)と絡めて後述する実施形態に示す。

【0030】さらに、課題(4)に関しては、PIDの他に、伝送路や端末の使用に関し、伝送路や端末の提供者などが設定するTIDと呼ぶデータを情報PPに付加することによって解決することができる。なお、TIDをPIDの中にも含むこともできる。TIDに関する具体的な例も後述する実施形態で詳細に説明する。

【0031】さらに、課題(5)に関しては、PID、TIDに利用の段階に応じた利用料金を記述し、PPCが示す金額がその利用料金以上ならば、CHECKは情報PPの利用を許可する。利用者は情報PPの利用段階を、必要に応じて、不図示のタッチパネルやキーボードなどによって設定す

る。CHECKは、時間や、その段階的な使用条件が設定または変更される度に、利用可否の判定を行う。なお、課題(5)に関する具体例も後述する実施形態に示す。

【0032】

【第2実施形態】以下、本発明にかかる第2実施形態の課金システムを説明する。なお、第2実施形態において、第1実施形態と略同様の構成については、同一符号を付して、その詳細説明を省略する。

【0033】図3は第2実施形態の課金方式を示す図で、PPCが現金である場合を示している。

【0034】課金部は、情報PPのPIDに示された利用料金を表示部に表示する。利用者は、利用料金表示に従い、PPCの受け口に所定の金銭（例えばコインや紙幣）を投入する。CHECKは、投入金額がPIDに示された料金を超えたとき、情報PPの利用を許可する。

【0035】また、時間に応じて料金が更新される場合、課金部は、その旨を表示部に表示し、利用者に追加料金を投入させるようにする。また、不図示の入力部などにより使用条件を設定する場合、課金部は、それに応じた料金を表示部に表示し、利用者に料金を投入させるようにする。つまり、CHECKは、時間や料設定された使用条件、追加投入された金額、PIDに記述された料金に基づき、再判定を行うように構成されている。

【0036】投入された金銭は、COIN BOXに格納され、情報提供者Pまたは料金の回収を行う機関により回収される。このとき、CNTに記録された情報PPごとの利用頻度情報も回収され、その利用頻度情報に応じてCOIN BOXから回収した金額が各情報提供者Pに分配される。勿論、提供する情報PPが一つであるなど、利用頻度情報が不要の場合は、CNTを省略することができ。

【0037】このように、本実施形態に示す現金を用いた課金方式により、情報提供者または料金分配者が、例えば、公衆電話ボックス、ゲームセンター、喫茶店、図書館などに利用者端末を設置すれば、設置された利用者端末を、多数の人が現金を用いて利用することができる課金システムを実現することができる。

【0038】

【第3実施形態】以下、本発明にかかる第3実施形態の課金システムを説明する。なお、第3実施形態において、第1実施形態と略同様の構成については、同一符号を付して、その詳細説明を省略する。

【0039】図4は第3実施形態の課金方式を示す図で、PPCがプリペイドカードの場合を示している。

【0040】利用者は、PPCの受け口にプリペイドカードを挿入する。CHECKは、挿入されたプリペイドカードの残高が、PIDに示される料金より多い場合には情報PPの利用を許可する。この場合、情報PPの利用料金が時間によって更新される場合も、プリペイドカードに十分な残高があれば継続して利用可能であるように、課金部は構成されている。

【0041】また、不図示の入力部などにより使用条件が設定または変更された場合も、それに応じた金額をプリペイドカードから差し引くように、課金部は構成されている。このような利用の可否判定は、時間や使用条件に応じて、CHECKが、プリペイドカードの残高およびPIDの記述に基づき再判定を行うように構成されたい。

【0042】なお、プリペイドカードの初期金額にも限界があるので、PPCの受け口はプリペイドカードを追加挿入することができる構成にし、複数のプリペイドカードを連続的に使用することができる構成にするのが望ましい。

【0043】テレホンカードなどと同様に、多種多様の販売店などで販売するようにすれば、プリペイドカードの入手は容易である。この場合、プリペイドカードの製造または販売会社が料金の分配者になり、情報提供者Pは、料金の分配者に対して登録を行うことにより、情報PPの利用に応じた料金の分配を受けることができる。勿論、プリペイドカードの販売店は、料金の分配者に含まれる。

【0044】利用に応じた料金の分配に関しては、課金部が通信インタフェース(I/F)を用いて利用情報と料金分配者に知らせる利用通知によって実現する。ただし、利用通知は、課金部がプリペイドカードから利用料金を差し引くときに限り出力されるように構成する。

【0045】通信I/Fは、情報PPを通信により入手する場合にも利用することができる。従って、図5に示すように、料金分配者や、複数の情報提供者および利用者は、ネットワーク接続されていることになり、料金分配者は利用通知に応じて、所定の料金を所定の情報提供者に分配する。

【0046】また、通信I/Fをもたない場合は、利用する情報PPに応じてプリペイドカードの種類を替えるという方法もある。この場合、CHECKは、利用される情報PPのPIDの記述と、プリペイドカードの種類とから利用可否を判定し、適切なプリペイドカードが挿入されていれば、情報PPの利用を可能にする。

【0047】また、情報PPの利用記録をプリペイドカードに記録する手段を課金部がもたせ、使用済みのプリペイドカードを回収することにより、利用に応じた料金の分配を行うこともできる。この場合、プリペイドカードの回収を促進するためには、例えば、プリペイドカードを交換する場合のカード代金と、交換ではない場合のカード代金とに差を付ける。つまり、交換の場合はカード残高に見合ったカード代金とし、交換ではない場合のカード代金はカード自体の代金を含むようにすればよい。ただし、それでも回収できない利用記録に対応する料金は、回収できた利用記録に応じた比率で分配するなどの処置を取る。

【0048】このように、本実施形態に示すプリペイドカードを用いた課金方式により、情報提供者はCD-ROM、

パソコン通信、インターネットなどを利用して、広範囲に情報を配布し、一方、料金分配者となる所定機関がプリペイドカードを複製し販売すれば、利用者は販売店などを通じてプリペイドカードを購入し、入手した情報を自宅その他の利用者端末で利用する課金システムが実現できる。

【0049】

【第4実施形態】以下、本発明にかかる第4実施形態の課金システムを説明する。なお、第4実施形態において、第1実施形態と略同様の構成については、同一符号を付し、その詳細説明を省略する。

【0050】図6は第4実施形態の課金方式を示す図で、書換が比較的容易な電気的または/および磁気的なデバイス、例えばフロッピディスク、ICカード、磁気カードをPPCに利用するものである。PPCに記録されている金銭情報は、銀行などの金融機関によって保証されたデータや、販売店を含む料金分配者によってのみ加算処理できる特殊なデータである。

【0051】情報PPの利用者は、PPCの受け口にPPCを挿入する。課金部のCHECKは、PPCから金銭情報を読み出し、その金額が情報PPのPIDに示された利用料金よりも多く、かつ、そのPPCの発行元である料金分配者に利用料金の請求が可能である場合に、情報PPの利用を許可する。勿論、情報PPの利用料金が時間単位の場合でも、PPCに残高がある限りは、継続して情報PPを利用することができる。また、不図示の入力部などにより使用条件を設定、変更する場合、課金部は、その設定、変更に応じてPPCから所定の料金を差し引く。つまり、CHECKは、時間や設定された使用条件、追加投入された金額、PIDに記述された料金に基づき、再判定を行うように構成されている。

【0052】この場合の金銭情報は、電子的に読み書き可能な情報であるから、課金部は、通信I/Fを介して所定の手続きを経て、料金分配者と金銭情報の入出力を行うことができる。

【0053】前述した第1および第2実施形態と異なり、本実施形態における情報PPの利用者は金銭を料金分配者に直接支払うわけではない。利用者と契約を結んだ銀行や金融機関（以後「料金立替者」と呼ぶ）が、料金分配者に対して利用者の金銭支払いを保証するものである。従って、図7に示すように、料金分配者、料金立替者、複数の情報提供者および利用者は、ネットワーク接続されていることになる。

【0054】さらに、前述した利用通知を、第3実施形態と同様に、通信I/Fを介して料金分配者へ送ることができる。情報PPの利用に応じた料金の分配が可能になる。この場合、利用料金を電子マネーとして、直接、料金分配者や情報提供者に送ることができる。

【0055】具体的には、次のような通信処理によって電子マネーの入金出金を実現することができる。ただ

し、課金部は、後述するような暗号処理部および認証処理部を有し、後述するTAなどで示すタイムスタンプを完全に管理する管理部を有する必要がある。これは、書換え可能なPPCを考慮して、金銭情報の不正な書き換えやPPCの複製を防止するための処置である。つまり、金銭情報を認証可能にし、タイムスタンプの管理によって金銭情報のコピーなどの不正に対抗するものである。

【0056】利用者をA、情報提供者をB、料金分配者をC、料金立替者をDとし、それぞれは署名可能な秘密鍵を秘密に保持し、通信相手はその署名を検査できる公開鍵を知っている（例えば、Aの秘密鍵をsa、公開鍵をpaとする）とする。ここで、AがBの提供する情報P1を利用する場合を考える。ただし、Xの鍵Yによる処理結果を(X)Yで表し、利用者の各処理、および鍵やタイムスタンプAの管理は、課金部内の安全性が保証された手段、または、各人の記憶や記録によるとする。

【0057】【金銭情報入手処理】

(1)利用者はAは、例えばa円分の金銭情報の入力要求に、自分の登録情報IA（例えば口座番号やクレジット番号）を付加し、その情報に秘密鍵saで署名したメッセージMAを料金分配者Cに送る。

MA = {A, {A, IA, a, TA} sa}

【0058】(2)料金分配者Cは、メッセージMAの署名を利用者のAの公開鍵paで検査し、正しい情報であることを確認する。正しい情報であることを確認すると、メッセージMAから取出した登録情報IAを用いて、料金立替者Dにa円の請求を行う。その請求が受け入れられると、基本単位e（例えば、情報PPが100円単位であれば100円）ごとに、金銭情報に料金分配者Cの署名鍵scで署名したメッセージMCを利用者のAに送る。ただし、メッセージMCには、TAと異なるタイムスタンプTCが付け加えられる。

MC = Σ {TA, {C, e, TC} sc} pa

【0059】(3)利用者端末の課金部は、メッセージMCのそれぞれを鍵paで復号し、さらに、料金分配者Cの公開鍵pcで署名を検査し、正しい情報であることを確認すると、{C, e, TC} scをPPCに記録する。

【0060】ただし、TAやTCはタイムスタンプであり、同じ送信者からの同じタイムスタンプをもつメッセージは不正な情報であるといえる。また、TAやTCは、タイムスタンプでなくても、シリアル番号や、偶然に一致することがない、または、少ない乱数でもよい。

【0061】【利用情報通知処理】

(1)利用者がAが情報P1の利用を希望するとき、PPCの残高がPIDに示される利用料金より大きければ、課金部は情報P1の利用を許可する。

【0062】(2)利用者がAが情報P1の利用を終了するとき、または、利用中に、課金部は利用料金分の金額をPPCの残高から引き落とす。

【0063】(3)このとき、利用者はAは、利用通知MDを料金分配者Cに送る。ただし、PPCから引き落とされた金額

をbとする。

MB = {A, B, {B, b, TB}^n}sa)

【0064】(4)料金分配者Cは、メッセージMBを検査し、正しい情報であることを確認すると、利用料b(またはその一部を除いた金額)を情報提供者Bへの分配金として支払う。

【0065】以上では、料金分配者と利用者の間における暗号方式は公開鍵暗号とする例を説明したが、予め鍵が共有されていれば共通鍵暗号を用いてもよいことは明らかである。また、タイムスタンプの時間によって、各メッセージの有効期間を定めることもできる。以上において、メッセージ内の並び順は順不同であり、A, Bなどで示す利用者の識別子やタイムスタンプは、必ずしも必要でない場合がある。さらに、上記の金銭情報入手処理および利用情報通知処理の手順は一例であり、電子的な情報を金銭情報として、利用者固有データを用いずに課金処理を行うものはいずれも本発明に含まれる。

【0066】また、利用者端末が通信I/Fをもたない場合、利用者は、販売店など料金分配者に向き、PPCに格納する金銭情報を入力してもらうことになる。また、課金部は、利用通知MBのような情報の利用記録をPPCに記録し、そのPPCに金銭情報を入力する際に、利用記録が回収されることによって、情報の利用に応じた料金を分配することができる。このような電子的な金銭情報は、前述したように、料金分配者だけが処理できる特殊なデータである。従って、通信I/Fをもたない利用者は、PPCを用いるためには必ず販売店など料金分配者を介する必要があるので、利用記録は必ず回収でき、利用に応じた料金の分配が可能である。

【0067】このように、本実施形態に示すフロッピディスクなどを用いた課金方式により、フロッピディスクドライブを備えたパーソナルコンピュータなどのような利用者端末では、PPCのための特別な受け口を必要としない。さらに、金銭情報の通信によるやり取りによってプリペイドカードの販売店を省略可能に、暗号および認証処理をソフト的に行うことにより、既存のネットワーク上で容易に実現可能な課金システムが構成できる。

【0068】

【第5実施形態】以下、本発明にかかる第5実施形態の課金システムを説明する。なお、第5実施形態において、第1実施形態と略同様の構成については、同一符号を付して、その詳細説明を省略する。

【0069】図8は第5実施形態の課金方式を示す図で、ICカードやPCMCIAのような電子的なカードをPPCに利用するものである。PPCに記録されている金銭情報は、銀行などの金融機関によって保証されたデータや、販売店を含む料金分配者によってのみ加算処理できる特殊なデータである。

【0070】情報PPの利用者は、PPCの受け口にPPCを挿入し、所定の手続き(暗証番号の入力など)によってPP

Cを動作可能にする。課金部のCHECKは、PPCから金銭情報を読み出し、その金額が情報PPのPIDに示された利用料金より多く、かつ、PPCの発行元である料金分配者に利用料金を請求が可能である場合に、情報PPの利用を許可する。勿論、情報PPの利用料金が時間単位の場合でも、PPCに残高がある限りは、継続して情報PPを利用することができる。また、不図示の入力部などにより使用条件を設定、変更する場合、課金部は、その設定、変更に応じてPPCから所定の料金を差し引く。つまり、CHECKは、時間や設定された使用条件、追加投入された金額、PIDに記録された料金に基づき、再判定を行うように構成されている。

【0071】この場合の金銭情報は、電子的に読み書き可能な情報であるから、課金部は、通信I/Fを介して所定の手続きを経て、料金分配者と金銭情報の入力を行うことができる。

【0072】前述した第1および第2実施形態と異なり、本実施形態における情報PPの利用者は金銭を料金分配者に直接支払うわけではない。利用者と契約を結んだ銀行や金融機関(料金代替者)が、料金分配者に対して利用者の金銭支払いを保証するものである。従って、図7に示したように、料金分配者、料金代替者、複数の情報提供者および利用者は、ネットワーク接続されていることになる。

【0073】さらに、前述した利用通知を、第3実施形態と同様に、通信I/Fを介して料金分配者へ送ることができ、情報PPの利用に応じた料金の分配が可能になる。この場合、利用料金を電子マネーとして、直接、料金分配者や情報提供者に送ることができる。

【0074】具体的には、次のような通信処理によって電子マネーの入金出金を実現することができる。ただし、通信や処理に関する安全性を考慮して、PPCに用いる電子的なカードは、セキュリティ機能としての暗証番号による所有者確認や、アクセス条件によるデータメモリへのアクセス制御や、後述するような暗号方式による暗号および認証処理を行う。このとき、暗号処理や認証処理に用いる秘密鍵は、アクセス制御されたメモリ領域に書込まれ、そのアクセス条件を満たす者(カード発行者や料金分配者など)しかアクセスできない。また、以下の課金動作もカード発行者または料金分配者以外は変更することができる。

【0075】利用者をA、情報提供者をB、料金分配者をC、料金代替者をDとし、料金分配者Cは各利用者に対して暗証番号のための秘密鍵を共有し(例えば、AとCの間の秘密鍵をsA、BとCの間の秘密鍵をsBとする)、料金分配者Cは署名のための秘密鍵sCを保持し、それに対応する署名の検査鍵pCを公開しているものとする。以下、利用者Aが情報提供者Bより提供される情報P1を利用する場合を考える。ただし、平文Xの鍵Yによる暗号文を(X)Yで表し、利用者Aの各処理は、すべて上述したようなセ

セキュリティ機能をもつPPC内で行われるものとする。

【0076】【金銭情報入手処理】

(1)利用者Aは、例えばa円分の金銭情報の入力要求に、料金立替者Dに対応する自分の登録情報IA（例えば口座番号やクレジットカード番号）を付加し、その情報を料金分配者Cに送る。

MA = {A, IA, A, a, TA} ~ SA

【0077】(2)料金分配者Cは、メッセージMAの暗号部分を利用者Aと共有する秘密鍵SAで復号し、登録情報IAを用いて、料金立替者Dにa円の請求を行う。その請求が受入れられると、金銭情報に料金分配者Cの署名鍵SCで署名したメッセージMCを利用者Aに送る。

MC = {TA, C, a, TC} ~ SC ~ SA

【0078】(3)利用者Aは、メッセージMCを署名鍵SAで復号し、さらに、署名鍵SCに対応する公開鍵PCで署名を検査し、正しい情報であることを確認すると、PPCにa円分の金銭情報を加算する。

【0079】ただし、TAやTCはタイムスタンプであり、同じ送信者からの同じタイムスタンプをもつメッセージは不正な情報であるといえる。また、TAやTCはタイムスタンプでなくても、シリアル番号や、偶然に一致することがない、または、少ない乱数でもよい。

【0080】【利用情報通知処理】

(1)利用者Aが情報P1の利用を希望するとき、PPCの残高がP1に示される利用料金より大きければ、課金部は情報P1の利用を許可する。

【0081】(2)利用者Aが情報P1の利用を終了するとき、または、利用中に、課金部は利用料金分の金額をPPCの残高から引き落とす。

【0082】(3)このとき、課金部は、利用通知MBを料金分配者Cに送る。ただし、PPCから引き落とされた金額をもととする。

MB = {A, IA, B, b, TB} ~ SA

【0083】(4)料金分配者Cは、このメッセージMBを検査し、正しい条であることを確認すると、利用料b（またはその一部を除いた金額）を情報提供者Bへの分配金として支払う。

【0084】次に、AとBの間の情報も暗号通信によってやり取りする場合、次の処理を前述した金銭情報入手処理と利用情報通知処理の間で行えばよい。ただし、料金分配者Cは情報提供者Bとも秘密鍵を共有しているとする。

【0085】【利用情報処理】

(1)利用者Aは、情報提供者Bとの会話履歴の生成を依頼するため、次のメッセージを料金分配者Cに送る。

MA' = {A, B, TA'}

【0086】(2)料金分配者Cは、会話履歴CKを生成し、次のメッセージを利用者Aに送る。

MC' = {TC', A, CK} ~ SB, TA', B, CK} ~ SA

【0087】(3)利用者Aは、メッセージMC'を秘密鍵SA

で復号し、{TC', A, CK} ~ SBを情報提供者Bに送る。

【0088】(4)情報提供者Bは、受信メッセージを署名鍵SBで復号し、会話履歴CKで暗号化した情報を利用者Aに送る。

【0089】(5)利用者Aは、会話履歴CKで暗号化情報を復号する。

【0090】以上では、処理を簡単にするために料金分配者と利用者の間における暗号方式は共通鍵暗号とする例を説明したが、前の実施形態と同様に、公開鍵暗号を用いてもよいことは明らかである。また、タイムスタンプの時間によって、各メッセージの有効期間を定めることもできる。以上において、メッセージ内の並び順は順不同であり、A, Bなどで示す利用者の識別子やタイムスタンプは、必ずしも必要でない場合がある。さらに、上記の金銭情報入手処理および利用情報通知処理の手順は一例であり、電子的な情報を金銭情報として、利用者固有データを問わずに課金処理を行うものはすべて本発明に含まれる。

【0091】また、利用者端末が通信I/Fをもたない場合、利用者は、販売店など料金分配者に向き、PPCに格納する金銭情報を入力してもらうことになる。また、課金部は、利用通知MBのような情報の利用記録をPPCに記録し、そのPPCに金銭情報を入力する際に、利用記録が回収されることによって、情報の利用に応じた料金を分配することができる。このような電子的な金銭情報は、前述したように、料金分配者だけで処理できる特殊なデータである。従って、通信I/Fをもたない利用者は、PPCを用いるためには必ず販売店など料金分配者を介する必要があるので、利用記録は必ず回収でき、利用に応じた料金の分配が可能である。

【0092】このように、本実施形態に示すICカードやPCMCIAなどの電子的なカードを用いた課金方式により、第4実施形態の課金システムをより安全にした課金システムを実現することができる。

【0093】

【第5実施形態】以下、本発明にかかる第5実施形態の課金システムを説明する。なお、第5実施形態において、第1実施形態と略同様の構成については、同一符号を付して、その詳細説明を省略する。

【0094】図9は第5実施形態の課金方式を示す図で、第5実施形態と同様に電子的な金銭情報を用い、料金分配者の不要な課金方式である。複数の利用者および情報提供者と、料金立替者とは、図10に示すように、ネットワーク接続されている。さらに、PPCとして用いる電子カードは、セキュリティ機能として暗証番号による所有者確認や、アクセス条件によるデータメモリへのアクセス制御や、後述するような暗号方式による暗号および認証を行うことができる。このとき、暗号処理や認証処理に用いる秘密鍵は、アクセス制御されたメモリ領域に書込まれている。また、以下の課金動作もカード発行者ま

たは料金分配者以外は変更することができない。

【0095】利用者A、情報提供者をB、料金立替者をDとし、それぞれは署名可能な秘密鍵を保持し、通信相手は署名を検査することができる公開鍵を知っているものとする。例えば、利用者Aの秘密鍵をsA、公開鍵をpAとする。ここで、利用者Aが情報提供者Bが提供する情報Piを利用する場合を考える。ただし、Xの鍵Yによる処理結果を「X」Yで表し、利用者Aにおける処理はすべて上述したようなセキュリティ機能をもつPPC内で行われる。

【0096】【金銭情報入手処理】

(1)利用者Aは、例えばa円分の金銭情報の入力要求に、自分の登録情報1A（例えば口座番号やクレジット番号）を付加し、その情報を料金立替者Dに送る。

MA = {A, {A, 1A, a, TA}^sA}

【0097】(2)料金立替者Dは、メッセージMAの署名を利用者Aの公開鍵pAで検査し、登録情報1Aが正しく、利用者Aに対してa円を支払可能であれば、a円に対応する金銭情報を秘密鍵sDで署名したメッセージMDを利用者Aに返す。

MD = {TA, {D, a, TD}^sD} sA

【0098】(3)利用者Aは、メッセージMDを公開鍵pAで検査し、さらに、料金立替者の公開鍵pDで署名を検査し、正しい情報であることを確認すると、PPCにa円分の金銭情報を加算する。

【0099】ただし、TAやTC1はタイムスタンプであり、同じ送信者からの同じタイムスタンプをもつメッセージは不正な情報であるといえる。また、TAやTC1は、タイムスタンプでなくても、シリアル番号や、偶然に一致することがない、または、少ない乱数でもよい。

【0100】【利用情報通知処理】

(1)利用者Aが情報Piの利用を希望するとき、PPCの残高がPiDiに示される利用料金より大きければ、課金部は情報Piに利用を許可する。

【0101】(2)利用者Aが情報Piの利用を終了するとき、または、利用中に、課金部は利用料金分の金額をPPCの残高から引き落とす。

【0102】(3)このとき、利用者Aは、利用通知MBを情報提供者Bに送る。ただし、PPCから引き落とされた金額をbとすると

MB = {A, B, {B, b, TB}^sA}

【0103】(4)情報提供者Bは、メッセージMBを検査し、正しい情報であることを確認すると、利用者Aの署名{B, b, TB}^sAを料金立替者Dに示し、b円の料金を受取る。

【0104】利用者と情報提供者の間の情報は暗号通信によってやり取りする場合、直接、相手の公開鍵を用いて暗号通信を行うこともできるが、情報量が多い場合は、次のように共通暗号化による暗号通信を行うこともできる。この場合、各利用者と情報提供者の間には、共通暗号化手段が共有されているとする。ただし、(1)(2)

において、AとBは逆であってもよい。

【0105】【情報利用情報処理】

(1)利用者Aは、情報提供者Bとの共通鍵CKの公開鍵pBで暗号化したメッセージを送る。

MA' = {A, B, CK, TA'}^pB

【0106】(2)情報提供者Bは、受信メッセージを秘密鍵sBで復号する。(3)情報提供者Bは、共通鍵CKにより共通暗号化した情報を利用者Aに送る。(4)利用者Aは、共通鍵CKで共通暗号化された情報を復号する。

【0107】以上では、説明を簡単にするために料金立替者、利用者、情報提供者の暗号方式は公開暗号とする例を説明したが、前述したように共通暗号化を用いてもよいことは明らかである。また、タイムスタンプの時間によって、各メッセージの有効期間を定めることもできる。以上において、メッセージ内の並び順は順不同であり、A、Bなどで示す利用者の識別子やタイムスタンプは、必ずしも必要でない場合がある。さらに、上記の金銭情報入手処理および利用情報通知処理の手順は一例であり、電子的な情報を金銭情報として、利用者固有データを用いずに課金処理を行うものはすべて本発明に含まれる。

【0108】おのうに、本実施形態に示す課金方式により、料金分配者が不要、すなわち利用者と情報提供者とが料金立替者を通して直接取引をする課金システムを実現することができる。また、この課金方式および課金システムは、将来実用化されると思われる、ある特殊なデータを金銭と同様に扱う電子マネーあるいはディジタルキャッシュに対してでも適用可能であることは明らかである。

【0109】

【第7実施形態】以下、本発明にかかる第7実施形態の課金システムを説明する。なお、第7実施形態において、第1実施形態と略同様の構成については、同一符号を付して、その詳細説明を省略する。

【0110】情報提供者により異なる鍵で暗号化された多くの情報が格納されたCD-ROMが、販売店を通じて安価に販売され、そのCD-ROMを購入した利用者からの依頼に応じて情報提供者が指定情報の暗号鍵を知らせる際に、その情報の利用代金を請求する課金方式が知られている。しかし、この方式は、CD-ROMを販売する販売店にとって媒体の販売利益は得られても、CD-ROMに格納された情報を販売したことに対する利益は得られないという問題がある。本発明で示すPPCによる課金方式を、レンタル的な情報の利用だけでなく、情報の買い取りに対して用いることにより上記の問題を解決することができる。

【0111】すなわち、利用者は、販売店でのCD-ROMを購入すると同時に、プリペイドカードなどのPPCも購入する。そして、利用者が、情報提供者との通信（電話などを含む）によって暗号鍵を知るときに、プリペイドカ

ードによる支払を指定することによって、情報提供者は、プリペイドカードを販売した販売店から情報の利用代金を回収することができる。この方法によれば、情報の利用代金も販売店を経由することになるので、販売店は情報利用に対する利益も得ることができる。

【0112】課金部は、PPCの残高を検査し、利用しようとする情報の料金以上の残高がある場合、その情報に対する暗号を復号し、かつ、PPCから料金を差し引くようにする。さらに、PPCは、その残高は換金できるようにし、情報提供者ごとに製作された販売店を通じてCD-ROMと同様に販売される。従って、この実施形態では料金分配者は不要である。

【0113】また、上述した各実施形態における利用情報通知処理を以下のようにすることで、プリペイドカードの利用情報通知処理も安全にすることができる。ただし、プリペイドカードには、プリペイドカードごとの識別番号IPと、それに対応した秘密鍵SPが登録されているものとする。

【0114】【利用情報通知処理】

(1)利用者Aが情報Pの利用を希望するとき、PPCの残高がPIDに示される利用料金より大きければ、課金部は情報Pの利用を許可する。

【0115】(2)利用者Aが情報Pの利用を終了するとき、または、利用中に、課金部は利用料金分の金額をPPCの残高から引き落とし、その結果をPPCに書込む。

【0116】(3)このとき、CHECKは、利用通知Mを情報提供者Bに送る。ただし、PPCから引き落とされた金額をbとする。

MB = {IP, b, b, IP, TID} SP

【0117】(4)情報提供者Bは、メッセージMを登録された秘密鍵SPで復号し、正しい情報であることを確認すると、利用料bの一部を販売店への分配金として支払う。

【0118】従って、プリペイドカードごとの識別番号IPと、それに対応した秘密鍵SPとを知るもの以外、この利用通知を生成することはできない。

【0119】

【第8実施形態】以下、本発明にかかる第8実施形態の課金システムを説明する。なお、第8実施形態において、第1実施形態と略同様の構成については、同一符号を付して、その詳細説明を省略する。

【0120】マルチメディアネットワークにおいては、情報提供者のほかに、図11に示すように、ネットワークそのものにあたる伝送路の提供者や、高品質な端末が要求されるので端末の提供者なども存在することが予想される。従って、利用者は、情報の利用だけでなく、伝送路や端末の利用についても料金を支払う必要がある。それらは別々の課金体系により処理されているものもあり、一つの課金体系によって処理された方が便利であり、かつ、使用する情報単位で課金される方が細かい課金が可

能である。

【0121】前述した各実施形態に示した課金方式は、情報提供者が設定するPIDと金銭情報であるPPCに基づいて課金され、その課金は利用に応じて直接、または、料金分配者を通じて情報提供者に分配されるものである。従って、伝送路や端末などの提供者がPIDに相当する情報を提供情報に付加することができる、同様の手法によって、情報提供者を含むすべての提供者に正しく料金を分配することができる。

【0122】図12は第8実施形態のマルチメディアネットワークに関するすべての提供者へ情報単位で料金を分配する課金方式を示す図である。

【0123】図12において、Pは情報提供者、PP1(またはPPj)は情報提供者Pにより提供される有償情報、PID1(またはPIDj)はPP1に固有の情報固有データ、PPCは金銭情報、CHECKは情報の利用可否を判定する手段である。さらに、TID1(またはTIDj)は伝送路や端末の提供者などによって設定される伝送路や端末の使用に関する付加データである。

【0124】情報提供者Pおよび/または各提供者は、有償情報PP1にPIDをはじめTIDなどのデータを付加する。なお、PIDやTIDはまとめて一つのデータとしてもよい。利用者端末で情報PPを利用する際は、必ず課金部を経由するように構成され、その課金部には金銭情報が記録されたPPCを挿入するためのPPCの受け口がある。

【0125】提供情報PPの利用要求が生じると、CHECKは、PID、TID、PPCの少なくとも一部の情報に基づき情報PPの利用可否を判定する。例えば、PIDとTIDに示された利用料金が、PPCの残高以内か否かなどのチェックである。CHECKの判定結果が可を示せば、利用者端末による情報PPの利用が可能になる。なお、情報PPの利用可否およびPID、TID、PPCに関する情報(情報PPの利用料金やPPCの残高など)は利用者端末に通知され、表示部に表示される。勿論、PIDやTIDに示された利用料金が時間単位の場合でも、PPCに残高がある限りは、継続して情報PPを利用することができる。また、不図示の入力部などにより使用条件を設定、変更する場合、課金部は、その設定、変更に応じてPPCから所定の料金を差し引く。つまり、CHECKは、時間や設定された使用条件、PIDおよびTIDに記述された料金に基づき、再判定を行うように構成されている。

【0126】本発明における金銭情報が記録されたPPCは、現金であってもよいし、テレホンカードのようなプリペイドカードであってもよいし、フロッピーディスク、ICカードやPCMCIAなどに格納された金銭と等価な電子情報であってもよい。

【0127】本発明では、利用者ごとの利用者固有データUSER IDの代わりに、金銭情報が記録された利用者に依存しないPPCによって情報PPの利用可否を判定する。従って、前述した実施形態と同様に、課題(1)から課題

(3)を解決することができ、ただし、図12では、説明を簡単にするために、通信1/Fに関する説明を省略としたが、他の実施形態と同様に通信1/Fを付加し、料金分配者や料金立替者と通信することもできる。

【0128】さらに、本実施形態によれば、TIDは提供者が異なるだけでPIDと同じ意味をもち、利用者は上記のようにTIDに関する料金をPPCから支払う。従って、料金分配者から、または通信により直接、伝送路や端末などの使用に応じた料金を各提供者に分配すれば、マルチメディアネットワークに関するすべての提供者に正当な料金を支払うことができ、課題(4)を解決することができ、

【0129】具体的には、情報PPの回線使用時間に応じた料金をTIDに記述することで、伝送路の提供者は回線使用時間に応じた料金を正当に得ることができる。さらに、使用時間、使用回線などの種別に対応する料金をTIDに記述しておけば、より細かな課金も可能である。このとき、伝送路の提供者は、情報提供者とネットワークとを接続する接続器などに、TIDを付加する処理を行わなければならない。なお、接続器はハブやゲートウェイのような伝送路中にあるものも含む。また、CPUや端末の使用料の場合も同様に、その使用時間や処理に応じた料金をTIDに記述しておけば、端末の提供者などはCPUや端末の使用料を正当に得ることができる。

【0130】以下では、種々の場合についての課金の具体的実施例を説明する。

【0131】

【画像圧縮に関する課金の実施例1】異なる解像度をもつ画像処理装置に対応したり、画像データベースでの画像検索を効率的に行うための符号化方式として階層符号化がある。以下、階層符号化についてその概要を説明する。

【0132】最初に、画像全体を大まかに表す縮小画像を符号化し、続いて、縮小画像を順次拡大するための差分情報を符号化する。その結果、異なる解像度に対応できるスケーラブルな符号化を実現することができる。例えば、モニターでは画素数の少ない縮小画像を高速表示し、プリンタではすべての情報を用いる画素数の多い詳細な画像を形成するなどが可能になる。

【0133】図13は階層符号データの一般的な概念を示す図である。図13において、「イメージの先頭」は一つの画像情報全体の始まりを示すヘッダ、「フレーム」のヘッダはフレーム1の始まりを示すビットパターン、「フレーム1」は原画像の最も縮小された画像を符号化した階層1の情報、「フレーム2のヘッダ」はフレーム2の始まりを示すビットパターン、「フレーム2」は階層1の画像を拡大するための差分情報である階層2の情報、…、「フレームnのヘッダ」はフレームnの始まりを示すビットパターン、「フレームn」は階層n-1の画像を拡大するための差分情報である階層nの情報、「イメージの

終端」は一つの画像情報全体の終わりを示す情報である。

【0134】代表的な階層符号化方式として、JPEGの階層符号化方式（ISO/IEC10918-1、10918-2またはITU-TT.81、T83）などが知られている。このような符号化技術は、マルチメディアネットワークにおいてよく用いられる技術である。

【0135】以下では、このような階層符号化による解像度に関する料金情報をTIDに記述する例を説明する。

【0136】解像度は、情報PPに固有でないデータである。すなわち、同じ一つの情報であっても伝送路のトラフィックや、利用者端末のモニタの解像度や、データ検索の精度などに応じて、伝送路を介して送られる情報の階層符号化による解像度は異なる。

【0137】そこで、TIDには、情報PPが送られるときの階層符号化の解像度と、それに関する料金などを記述する。例えば、同じ情報PPでも、階層1の荒い解像度で伝送する場合と、階層nの精密な解像度で伝送する場合とで、その料金は異なる。また、階層の精密な解像度まで送り、それを復号または表示するときに、復号器や表示部の能力に応じた階層までの解像度とすることもできる。この場合、TIDには全階層に対する料金が記述され、使用した階層に応じて課金することもできる。

【0138】図14は本実施例における課金動作を説明する図である。図14において、Pは情報提供者、PP1（またはPPj）は情報提供者Pによって提供される情報、PID1（またはPIDj）はPP1に固有の情報固有データ、TID1（またはTIDj）は情報PP1に固有ではない付加データ、Pは金銭情報、CHECKは情報PPの利用可否を判定する手段である。

【0139】課金部のCHECKは、PPCの受け口に入力されたPPCから金銭情報を読出し、その残金がPID、TIDに示された料金より多く、PPCに利用料金を請求可能な場合に、情報PPの利用を許可する。ただし、全階層データを受信し、指定された解像度で復号する場合は、指定する解像度を課金部に入力するキーボードなどの入力部があり、その指定解像度によりTIDに関する料金が決定される。さらに、情報PPのPIDによる料金や、TIDによる料金などが、時間や使用条件（利用解像度など）によって更新される場合も、PPCの残金以内であれば、継続して利用可能であるように構成する。つまり、CHECKは、時間や設定された使用条件、PID、TIDに記述された料金に基づき、再判定を行うように構成されている。また、PPCは、他の実施形態で説明したように、現金、プリペイドカードなどの磁気カード、ICカードなどを利用することができる。

【0140】CHECKにより情報PPの利用が許可された場合、情報PPとともにTIDに記述された解像度に関するデータが階層符号化処理部に送られ、階層符号化処理部は、その解像度に対応した階層符号の復号処理を行う。

21

また、情報PPがすべての階層データを含み、利用者または端末が復号する解像度を指定する場合、情報PPとともに指定された解像度が階層符号化処理部に送られ、階層符号化処理部は、指定された解像度に対応する階層までの復号処理を行う。この階層符号化処理部は、前述したJPEGの階層符号化方式に示されるような公知の処理装置でよい。

【0141】また、料金の分配に関しても、他の実施形態と同様の方法を用いることができ、そのために、図14に通信1/Fを付加することもできる。

【0142】また、階層符号化処理部は、情報提供者Pと異なる伝送路の提供者などが開発することも多い。この場合、伝送路の提供者は、TIDとともに階層符号化処理部を情報提供者Pに提供する。TIDおよび階層符号化処理部を提供された情報提供者Pは、それらをPIDと一緒に情報PPに付属させて利用者に提供する。また、情報提供者Pとネットワークとが、伝送路の提供者により提供される接続器などによって接続されるならば、その接続器を介して、PIDを含む情報PPが伝送路に送り出されるときに、その接続器で情報PPに階層符号化を施すとともに、階層符号化を施した情報PPにTIDおよび階層符号化処理部を付加することもできる。なお、接続器は、ハブのように伝送路の中にあってもよい。

【0143】また、情報センタのようなある機関が情報提供者Pから情報PPを集め、一括して情報PPを提供する場合、その情報センタが単独に、あるいは、伝送路の提供者と共同して、情報PPに階層符号化を施しTIDを設定することもできる。なお、情報センタは、伝送路の提供者や料金分配者を兼ねる場合もある。

【0144】料金の分配に関しては、利用者から料金分配者へ、PIDに関する情報のほかに、TIDに関する情報も通知すれば、他の実施形態と同様に、料金分配者は通知されたTIDに関する情報に応じた料金を伝送路の提供者などに分配する。従って、料金分配の仕組みは、他の実施形態で述べた方法を用いることができる。勿論、階層符号化処理部の開発者が伝送路の提供者でない場合、階層符号化処理部の提供者である開発者にも、正当な料金が分配されることは言うまでもない。

【0145】

【画像圧縮に関する課金の実施例2】動画情報を効率よく蓄積・伝送するための符号化方式としてMPEGが知られている。MPEG符号化方式は、動画画像の高効率符号化を行うことを目的とする国際標準で、動画情報の周波数特性や人間の視覚特性を利用するとともに、動画画像特有の時間軸方向の冗長度を利用して、いっそうの高効率符号化を行う。MPEG方式には、デジタルストレージメディア用に転送レートを最大1.5MbpsとしたMPEG1と、伝送レートの上限をなくし、双方向デジタルマルチメディア機器、デジタルVTR、ATV(Advanced TV)、光ファイバネットワークなどのすべての伝送系で用いられることを企

22

図したMPEG2がある。MPEG1とMPEG2の基本的なアルゴリズムはほぼ同じであるので、MPEG1をベースとしてその符号化方式の原理およびデータ構造について説明する。

【0146】まず、MPEGによる高効率符号化方式の原理について説明する。MPEG方式においては、フレーム間の差分を取ることで時間軸方向の冗長度を落とし、これによって得られた差分データをDCTおよび可変長符号化処理して空間方向の冗長度を落とし、これによって全体として高効率符号化を実現する。時間軸方向の冗長度については、動画の場合は連続したフレームの相関が高いことに着目し、符号化しようとするフレームと時間的に先行または後行するフレームとの差分を取ることで冗長度を落とすことが可能になる。

【0147】そこで、MPEGでは、図15に示すように、専らフレーム内で符号化するモードで得られるイントラ符号化画像(I-ピクチャ)のほかに、時間的に先行するフレームとの差分値を符号化する前方予測符号化画像(P-ピクチャ)と、時間的に先行するフレームまたは後行するフレームとの差分値、あるいは、それらフレームからの補間フレームとの差分値の内、最もデータ量が少ないものを符号化する両方向予測符号化画像(B-ピクチャ)とを有し、これらの符号化モードによる各フレームを所定の順序で組み合わせる。

【0148】MPEGにおいては、上述したI-ピクチャ、P-ピクチャ、B-ピクチャをそれぞれ一枚、四枚、十枚で二単位(GOP)とし、先頭にI-ピクチャを配し、続いて、二枚のB-ピクチャおよび一枚のP-ピクチャを繰返し配置する組み合わせを推奨している。一定周期でI-ピクチャを配置することにより、動画の逆方向再生や、GOPを単位とする部分再生を可能とするとともに、エラー伝播の防止を図っている。なお、フレーム中で新たな物体が現れた場合は、時間的に先行するフレームとの差分を取るよりも後行するフレームとの差分を取った方が、その差分値が少なくなる場合がある。そこで、MPEGでは上述のような両方向予測符号化を行い、より高効率な符号化を行う。

【0149】さらに、MPEGでは動き補償を行う。すなわち、8×8画素のブロックを輝度データについて4ブロック、色差データについて2ブロック集めた所定ブロック(マクロブロック)単位に、先行または後行フレームの対応ブロック近傍のマクロブロックとの差分をとり、一番差分が小さいマクロブロックを探索することによって動きベクトルを検出し、この動きベクトルをデータとして符号化する。復号の際は、この動きベクトルを用いて先行または後行フレームの対応マクロブロックデータを抽出し、これにより動き補償を用いて符号化された符号データの復号を行う。このような動き補償に際しては、時間的に先行するフレームを一旦符号化した後、再度、復号したフレームを得て先行フレームとし、このフレームにおけるマクロブロックと符号化しようとするフレーム

のマクロブロックとを用いて動き補償を行う。なお、MPEG1はフレーム間の動き補償を行うが、MPEG2はフィールド間の動き補償を行う。このような動き補償によって得られた差分データおよび動きベクトルは、先に説明したようなDCTおよびハフマン符号化によって、さらに高効率符号化される。

【0150】次に、このMPEGデータの構造について説明する。MPEGデータは、ビデオシーケンス層、GOP層、ピクチャ層、スライス層、マクロブロック層、ブロック層からなる階層構造で構成されている。以下、下層から順に説明する。

【0151】まず、ブロック層は、先のJPECと同様に、画度データおよび色差データごとに8×8画素でそれぞれ構成され、この単位ごとにDCTが行われる。

【0152】マクロブロック層は、上述した8×8画素のブロックを画度データについては4ブロック、色差データについては各1ブロックにまとめ、マクロブロックヘッダを付したもので、MPEG方式ではこのマクロブロックを後述する動き補償および符号化の単位とする。マクロブロックヘッダは、各マクロブロック単位の動き補償および量子化ステップの各データ、および、各マクロブロック内の六つのDCTブロック(Y0, Y1, Y2, Y3, Cr, Cb)がデータを有するのかがかのデータを含む。

【0153】スライス層は、画像の走査順に連なる一つ以上のマクロブロックおよびスライスヘッダで構成され、同一スライス層内の一連のマクロブロックにおける量子化ステップを一定とすることができ、なお、スライスヘッダは、各スライス層内の量子化ステップに関するデータを有し、各マクロブロックに固有の量子化ステップデータがない場合には、そのスライス層内の量子化ステップを一定とする。また、先頭のマクロブロックは直流成分の差分値をリセットする。

【0154】ピクチャ層は、スライス層を1フレーム単位で複数集めたものであり、ピクチャスタートコードなどからなるヘッダと、これに続く、一つまたは複数のスライス層とから構成される。また、ヘッダには、画像の符号化モードを示すコード(符号化識別符号)や動き検出の精度(画素単位か半画素単位か)を示すコードが含まれる。

【0155】GOP層は、グループスタートコードや、シーケンスの最初からの時間を示すタイムコードなどを含むヘッダと、これに続く、複数のフレーム、BフレームまたはPフレームから構成される。

【0156】ビデオシーケンス層は、シーケンススタートコードから始まってシーケンスエンコードで終了し、その間に画像サイズやアスペクト比などの復号に必要な制御データおよび画像サイズなどが同じ複数のGOPに配列される。

【0157】上記のようなデータ構造をもつMPEG方式はビットストリームも規定されている。なお、このような

符号化技術は、マルチメディアネットワークにおいてよく用いられる技術である。

【0158】以下では、このようなMPEGによるピクチャ情報がTIDに記述された例を説明する。

【0159】ピクチャ情報は情報PPに固有でないデータである。すなわち、同じ一つの情報であっても、伝送路のトラフィックや、利用者のモニタの解像度などに応じて要求されるMPEGの符号化効率は異なる。そこで、TIDには、情報PPが送られるときのMPEGのピクチャに関する情報と、それに関する料金などが記述されるものとする。

例えば、同じ情報でも、P-ピクチャやB-ピクチャの伝送を少なくしたコマ送りの動的な画像の伝送に対する料金と、すべてのピクチャを用いる動画像の伝送に対する料金とでは、TIDに記述される料金は異なる。また、すべてのピクチャを伝送し、それを復号または表示する際に、復号器や表示部の能力に応じて指定されたピクチャによる復号を行うこともできる。この場合、TIDには、全ピクチャに対する料金が示され、使用したピクチャに応じて課金されることになる。

【0160】図16は本実施例における課金動作を説明する図である。図16において、Pは情報提供者、PPi(またはPPj)は情報提供者Pにより提供される情報、PIDi(またはPIDj)は情報PPiに固有の情報固有データ、TIDi(またはTIDj)は情報PPiに固有ではない付加データ、PPCは金銭情報、CHECKは情報PPの利用可否を判定する手段である。

【0161】利用者はPPCの受け口にPPCを挿入する。課金部のCHECKは、PPCから金銭情報を読み出し、PPCの残高がPID, TIDに示された料金より多く、PPCに利用料金を請求可能である場合に情報PPの利用を許可する。ただし、全ピクチャが伝送され、指定ピクチャにより復号を行う場合は、指定ピクチャを示す情報を課金部に入力するキーボードなどの不図示の入力部があり、それによってTIDに関する料金が判定される。さらに、情報PPのPIDによる利用料金およびTIDによる利用料金が時間単位、あるいは、使用条件(利用解像度など)が変わる場合も、PPCの残高がある限りは、継続して情報PPを利用することができる。つまり、CHECKは、時間や設定された使用条件、PID, TIDに記述された料金、PPCの残高に基づき、再判定を行うように構成されている。また、PPCは、他の実施形態で説明したように、現金、プリペイドカードなどの磁気カード、ICカードなどよい。

【0162】CHECKにより情報PPの利用が許可された場合、情報PPとともにTIDに記されたピクチャに関するデータがMPEG処理部に送られ、MPEG処理部はそのピクチャに対応した復号処理を行う。また、情報PPがすべてのピクチャを含み、利用者または端末から復号するピクチャが指定される場合も、情報PPとともにその指定情報がMPEG処理部に送られ、MPEG処理部は指定ピクチャに対応する復号処理を行う。このMPEG処理部は公知の処理装置で

ある。

【0163】また、料金の分配に関しては、他の実施形態と同様の方法を用いることができる。そのために、図16に示す構成に通信I/Fを付加することもできる。

【0164】また、階層符号化処理部は、情報提供者Pと異なる伝送路の提供者などが開発することも多い。この場合、伝送路の提供者は、TIDとともに階層符号化処理部を情報提供者Pに提供する。TIDおよび階層符号化処理部を提供された情報提供者Pは、それらをPIDと一緒に情報PPに付属させて利用者に提供する。また、情報提供者Pとネットワークとが、伝送路の提供者により提供される接続器などによって接続されるならば、その接続器を介して、PIDを含む情報PPが伝送路に送り出されるときに、その接続器で情報PPに階層符号化を施すとともに、階層符号化を施した情報PPにTIDおよび階層符号化処理部を付加することもできる。なお、接続器は、ハブのように伝送路の中にあってもよい。

【0165】また、情報センタのようなある機関が情報提供者Pから情報PPを集め、一括して情報PPを提供する場合、その情報センタが単独に、あるいは、伝送路の提供者と共同して、情報PPに階層符号化を施しTIDを設定することもできる。なお、情報センタは、伝送路の提供者や料金分配者を兼ねる場合もある。

【0166】料金の分配に関しては、利用者から料金分配者へ、PIDに関する情報のほかに、TIDに関する情報も通知すれば、他の実施形態と同様に、料金分配者は通知されたTIDに関する情報に応じた料金を伝送路の提供者などに分配する。従って、料金分配の仕組みは、他の実施形態で述べた方法を用いることができる。勿論、階層符号化処理部の開発者が伝送路の提供者でない場合、階層符号化処理部の提供者である開発者にも、正当な料金が分配されることは言うまでもない。

【0167】また、本実施例では、符号化の例としてMP3を取り上げたが、時間軸上の差分を用いた符号化に関して、PPCを用いて課金する方法は、すべて本実施形態に含まれる。

【0168】

【暗号技術の課金に関する実施例】以下では、提供される情報を指定した利用者以外に利用させないための暗号技術に対する課金に関して説明する。

【0169】マルチメディアネットワークは種々の情報を取扱うために、情報の種類に応じて要求される処理速度や安全性が大きく異なる。例えば、動画のような大容量で、高遅リアルタイム性が要求されるデータの場合は、高遅な暗号処理が要求されるし、文書やソフトウェアに代表される小容量で、リアルタイム性が要求されないデータの場合は、暗号処理速度を速くして、暗号処理に関する負荷を軽減することが望まれる。また、動画のようなデータは、スクランブル程度の安全性の低い暗号処理でよい場合が多く、文書やソフトウェアのような

データの場合は、安全性の高い暗号処理が望まれる場合が多い。従って、要求される処理速度や安全性に対応した課金が実現されることが望まれる。

【0170】以下では、暗号の処理速度や強度に対する料金がTIDに記述された例を説明する。

【0171】図17は本実施例における課金動作を説明する図である。図17において、Pは情報提供者、PP1（またはPPj）は情報提供者Pにより提供される情報、PIDi（またはPIDj）は情報PPiに固有の情報固有データ、TIDi（またはTIDj）は情報PPiに固有でない付加データ、PPCは金銭情報、CHECKは情報PPの利用可否を判定する手段である。

【0172】利用者はPPCの受け口にPPCを挿入する。課金部のCHECKは、PPCから金銭情報を讀出し、PPCの残高がPID、TIDに示された料金より多く、PPCに利用料金を請求可能である場合に情報PPの利用を許可する。ただし、金ピクチャが伝送され、指定ピクチャにより復号を行う場合は、指定ピクチャを示す情報を課金部に入力するキーボードなどの不図示の入力部があり、それによってTIDに関する料金が判定される。さらに、情報PPのPIDによる利用料金およびTIDによる利用料金が時間単位、あるいは、使用条件（暗号の処理速度や強度など）によって変わる場合も、PPCに残高がある限りは、継続して情報PPを利用することができる。つまり、CHECKは、時間や設定された使用条件、PID、TIDに記述された料金、PPCの残高に基づき、再判定を行うように構成されている。また、PPCは、他の実施形態で説明したように、現金、プリペイドカードなどの磁気カード、ICカードなどであり。

【0173】CHECKにより情報PPの利用が許可された場合、情報PPとともにTIDに記された暗号の処理速度や強度に関するデータが暗号処理部に送られ、暗号処理部はその処理速度や強度に対応した暗号処理を行う。異なる処理速度や強度に応じて暗号処理を行う暗号処理部の構成は、本出願人が先に申請した特願平7-165187号に詳述されている。

【0174】また、料金の分配に関しては、他の実施形態と同様の方法を用いることができる。そのために、図17に示す構成に通信I/Fを付加することもできる。

【0175】また、暗号処理部は、情報提供者Pと異なる伝送路の提供者などが開発することも多い。この場合、伝送路の提供者は、TIDとともに暗号処理部を情報提供者Pに提供する。TIDおよび暗号処理部を提供された情報提供者Pは、それらをPIDと一緒に情報PPに付属させて利用者に提供する。また、情報提供者Pとネットワークとが、伝送路の提供者により提供される接続器などによって接続されるならば、その接続器を介して、PIDを含む情報PPが伝送路に送り出されるときに、その接続器で情報PPに暗号処理を施すとともに、暗号化した情報PPにTIDおよび暗号処理部を付加することもできる。な

お、接続器は、ハブのように伝送路の中にあってもよい。

【0176】また、情報センタのようなある機関が情報提供者Pから情報PPを集め、一括して情報PPを提供する場合、その情報センタが単独に、あるいは、伝送路の提供者と共同して、情報PPに暗号化を施しTIDを設定することもできる。なお、情報センタは、伝送路の提供者や料金分配者を兼ねる場合もある。

【0177】料金の分配に関しては、利用者から料金分配者へ、PIDに関する情報のほかに、TIDに関する情報も通知されたいTIDに関する情報に応じた料金を伝送路の提供者などに分配する。従って、料金分配の仕組みは、他の実施形態で述べた方法を用いることができる。勿論、暗号処理部の開発者が伝送路の提供者でない場合、暗号処理部の提供者である開発者にも、正当な料金が分配されることは言うまでもない。

【0178】また、本実施例では、暗号処理部として本出願人が先に出願した特願平7-165187号を取り上げたが、異なる処理速度や強度に応じて暗号処理を行う暗号処理部であればよく、PPCを用い、暗号の処理速度や強度に応じて課金する方法は、すべて本実施形態に含まれる。

【0179】

【暗号の種類に応じた課金の実施例】前記の実施例では暗号の処理速度や強度に応じて課金する方法を説明したが、図18に示すように、暗号の処理速度や強度だけでなく暗号の種類(RSA, FEAL, DES, ...)も異なるネットワークの場合は、暗号の種類に応じた課金を実現することが重要である。この場合、使用する暗号の種類に応じた料金がTIDに記述されていれば、それに応じた料金をPPCから徴収することにより、種々の暗号に応じた課金が実現できることは明らかである。ただし、情報PPはTIDに記された暗号によって暗号化されているものとする。

【0180】さらに、前記の実施例と同様に、各暗号について、暗号の処理速度や強度に応じた細かい設定がTIDに記述されている。この場合、図17に示した構成により前記の実施例と同様に実現可能であることは明らかである。ただし、図17に示す暗号処理部は、各利用者端末が備える暗号処理部である。

【0181】また、各利用者端末が、情報PPの種類に応じて、使用する暗号を選択できる場合に対応する課金も考えられる。このような使用する暗号を選択できる暗号処理部は、本出願人が先に出願した特願平7-165392号に示されている。従って、図17に示す暗号処理部を特願平7-165392号に示される暗号処理部にすれば、図17と同様の構成により暗号を選択する場合に対応する課金も実現できる。このとき、TIDには、すべての暗号の種類と、それに対応する料金とが記述され、使用した暗号に応じたTIDに基づく課金が行われる。勿論、各暗号ごとに、

課金に関する細かい設定をTIDに記述することもできる。

【0182】

【画像品位に対する課金の実施例】本実施例は、情報PPの画像品位に対して課金するものである。画像品位とは、単位時間当りのフレーム数、画素数、画素それぞれの色度、彩度、明度、といった尺度のダイナミックレンジおよび階調などである。各項目が、より広いダイナミックレンジと、より細かい階調をもつほど、画像品位は高くなる。以下では、画像品位の各項目をTIDに記述する例を説明する。

【0183】画像品位を示すこれらの項目は情報に固有でないデータである。すなわち、同じ一つの情報であっても伝送路のトラフィックや、利用者端末のモニタの解像度や、データ検索の精度などに応じて、伝送路を介して送られる情報の画像品位は異なる。

【0184】そこで、TIDには、情報PPが送られるときの画像品位と、それに関する料金などを記述する。例えば、同じ情報PPでも、解像度の低い情報を伝送する場合と、解像度の細かい情報を伝送する場合とで、その料金は異なる。また、最高の画像品位で送り、必要に応じた画像品位の画像を表示することもできる。この場合、TIDには全画像品位に対する料金が記述され、使用した画像品位に応じて課金することもできる。

【0185】図19は本実施例における課金動作を説明する図である。図19において、Pは情報提供者、PP1（またはPPj）は情報提供者Pによって提供される情報、PIDi（またはPIDj）はPP1に固有の情報固有データ、TIDi（またはTIDj）は情報PP1に固有ではない付加データ、Pは金銭情報、CHECKは情報PPの利用可否を判定する手段である。

【0186】課金部のCHECKは、PPCの受け口挿入されたPPCから金銭情報を読出し、その残金がPID、TIDに示された料金より多く、PPCに利用料金を請求可能である場合に、情報PPの利用を許可する。ただし、全画像品位のデータが伝送され、指定の画像品位で表示する場合は、指定画像品位を示す情報を課金部に入力するキーボードなどの不図示の入力部があり、それによってTIDに関する料金が判定される。さらに、情報PPのPIDによる利用料金およびTIDによる利用料金が時間単位、あるいは、使用条件（画像品位など）が変わる場合も、PPCに残高がある限りは、継続して情報PPを利用することができる。つまり、CHECKは、時間や設定された使用条件、PID、TIDに記述された料金、PPCの残高に基づき、再判定を行うように構成されている。また、PPCは、他の実施形態で説明したように、現金、プリペイドカードなどの磁気カード、ICカードなどである。

【0187】CHECKにより情報PPの利用が許可された場合、情報PPとともにTIDに記された画像品位に関するデータが画像表示部に送られ、画像表示部はその画像品位

の画像を表示する。また、情報PPがすべての画像品位のデータを含み、利用者または端末から表示する画像品位が指定される場合も、情報PPとともにその指定情報が画像表示部に送られ、画像表示部は指定画像品位の画像を表示する。

【0188】また、料金の分配に関しては、他の実施形態と同様の方法を用いることができる。そのために、図19に示す構成に通信1/を付加することもできる。

【0189】また、画像表示部は、情報提供者Pと異なる伝送路の提供者などが開発することも多い。この場合、伝送路の提供者は、TIDとともに画像表示部を情報提供者Pに提供する。TIDおよび画像表示部を提供された情報提供者Pは、それらをPIDと一緒に情報PPに付属させて利用者に提供する。また、情報提供者Pとネットワークとが、伝送路の提供者により提供される接続器などによって接続されるならば、その接続器を介して、PIDを含む情報PPが伝送路に送り出されるときに、その接続器で情報PPにTIDおよび画像表示部を付加することもできる。なお、接続器は、ハブのように伝送路の中にあってもよい。

【0190】また、情報センタのようなある機関が情報提供者Pから情報PPを集め、一括して情報PPを提供する場合、その情報センタが単独に、あるいは、伝送路の提供者と共同して、情報PPに画像表示部およびTIDを設定することもできる。なお、情報センタは、伝送路の提供者や料金分配者を兼ねる場合もある。

【0191】料金の分配に関しては、利用者から料金分配者へ、PIDに関する情報のほかに、TIDに関する情報も通知すれば、他の実施形態と同様に、料金分配者は通知されたTIDに関する情報に応じた料金を伝送路の提供者などに分配する。従って、料金分配の仕組みは、他の実施形態で述べた方法を用いることができる。勿論、階層符号化処理部の開発者が伝送路の提供者でない場合、階層符号化処理部の提供者である開発者にも、正当な料金が分配されることは言うまでもない。

【0192】上述した実施例では、回線や利用者端末、画像圧縮、暗号、画像品位などに関して課金する方法を説明した。本発明にかかる課金方式は、TIDに課金される対象も記述するなど、TIDの形式を規定しておくことにより、回線や利用者端末、画像圧縮、暗号、画像品位などが混在するネットワークに対しても適用できる。

【0193】また、PIDやTIDに処理の種類を記述するなどの形式を規定しておくことにより、本発明の課金方法は、前述した処理以外の種々の処理に応用することができることは明らかであり、前述した情報提供者以外の、ネットワークに関する種々の情報を提供する提供者も自由に参入できる柔軟性の高い課金方法であることは明らかである。

【0194】また、前述した実施例の暗号の処理速度に応じた課金は、暗号だけでなく画像符号化などの種々の

処理における処理速度に適用できることは明らかである。また、安全性も暗号の強度だけでなく、アクセス制御など種々の安全性に対して適用することも明らかである。

【0195】また、TIDは、情報PPとともにやり取りなくとも、特定の形式のデータとして単独にやり取りし、TIDに示される料金がPPCの残高以下ならば、情報PPを伝送した後、情報PPの利用に対してPIDに関する課金が行われてもよい。

【0196】さらに、図20に示すように、PIDも特定の形式のデータとして、TIDと同様に単独でやり取りしてもよい。この場合、PIDとTIDに関する料金がPPCの残高以内のときだけ、情報PPが伝送されるようにすれば、伝送路を効率的に使用することができる。

【0197】また、図21に示すように、例えばTIDが利用者端末に固有のデータである場合、そのTIDは前述のようにネットワークを介してやり取りされなくとも、その利用者端末にTIDの格納部があり、CHECKが情報PPの利用の可否を判定する際、格納されたTIDに関するデータをチェックすれば、同様の課金処理が実行できることも明らかである。TIDは、情報PPに固有のデータではないので、これは利用者端末に限らず、TIDに固有の部分に対しても有効である。

【0198】また、零（無料）というのも料金の中に含まれる。従って、情報PPまたはその一部（階層符号化における低解像度画像など）の中には、無料で利用することもできるものもある。

【0199】

【第9実施形態】以下、本発明にかかる第9実施形態の課金システムを説明する。なお、第9実施形態において、第1実施形態と略同様の構成については、同一符号を付して、その詳細説明を省略する。

【0200】上述した各実施形態においては、情報ネットワークの利用に関して、利用者により利用料が支払われる課金システムを説明した。

【0201】しかし、現在のTVなどのネットワークでは、利用者は、特定の局を除いて無料で情報を利用することができ、その情報PPに関する費用（TV局の利益などを含む）はスポンサと呼ばれる企業などが支払うシステムになっている。これは、情報には、費用を負担しても利用者に見せたい情報、例えばCMなどが存在することを示している。以下では、利用者のほかに、情報PPの利用料金を支払うスポンサが存在することが可能な、図22に示すようなネットワークにおける課金システムを説明する。

【0202】情報提供者に費用が直接支払われる場合、情報提供者は支払われた費用内で情報（番組）を制作する必要がある。しかし、スポンサが存在する場合、情報提供者は、スポンサから得られる費用に加え、利用者への課金を考慮して情報を制作することができる。つま

り、情報の制作費とスポンサから得られる費用の差額を、PIDおよびTIDを利用して利用者に課金するわけである。これにより、情報提供者は、スポンサから得られる費用だけに依存せずに情報を制作することができ、利用者は比較的安価に、その情報を利用することができる。

【0203】スポンサは、費用とともにCMを情報提供者に渡し、または、費用とともにCMの制作を情報提供者に依頼する。情報提供者は、スポンサから得られた費用に応じて、情報にCMを挿入する。

【0204】提供される情報には、スポンサのCMが含まれることになるが、PID、TIDにCMの量に応じた料金を設定すれば、利用者は、高価だがCM枚数の密度の高い情報を利用することもできるし、CMは多いものの非常に安価（極端な場合は無料）な情報を利用することもでき、種々の場合を選択することができる。なお、情報提供者が、利用者からPID、TIDに記された料金を徴収する仕組みは、他の実施形態と同様である。

【0205】また、スポンサは、予め費用を支払わずに、情報の利用、つまりCMが再生された数に応じて費用を支払う場合、以下のような課金システムを構成することができる。なお、スポンサが設定することができるCM視聴に関する負担額を示す情報をCIDとするが、これはTIDと同様に提供情報に依存しないが付加されることのできる情報である。この場合、スポンサのCIDに記述された料金は、情報提供者のPIDやTIDに記述された料金とは異なり、PPCから徴収されるものではなく、むしろPPCに加算されるものである。

【0206】図23は本実施形態における課金動作を説明する図である。図23において、Pは情報提供者、PP1（またはPPj）は情報提供者Pにより提供される情報、PID1（またはPIDj）は情報PP1に固有の情報固有データ、TID1（またはTIDj）は情報PP1に固有ではない付加データ、CID1（またはCIDj）は情報PP1に固有ではない付加データに関するデータ、PPCは金銭情報、CHECKは情報PPの利用可否を判定する手段である。

【0207】利用者はPPCの受け口1にPPCを挿入する。課金部のCHECKは、PPCから金銭情報を読み出し、PPCの残高がPID+TID-CIDに示される料金より多く、PPCに利用料金を請求可能である場合に情報PPの利用を許可する。さらに、情報PPのPIDによる利用料金およびTIDによる利用料金が時間単位、あるいは、使用条件が変わる場合も、PPCに残高がある限りは、継続して情報PPを利用することができる。また、CMの再生（視聴）回数などによりCIDに記述された料金が、PPCに加算されるように構成することもできる。また、PPCは、他の実施形態で説明したように、現金、プリペイドカードなどの磁気カード、ICカードなどであり、

【0208】この課金システムにおいては、スポンサの費用負担は、利用者が情報PPを利用する際に生じるので、利用頻度が高く宣伝効果の大きい情報PPにおけるス

ポンサの負担は多く、利用頻度が低く宣伝効果の小さい情報PPにおけるスポンサの負担も少なくて済む、という正当な費用負担を実現することができる。

【0209】情報PPへのCMの挿入は、利用者がCM付きの安価な情報PPを望むとき、その情報PPの入手とネットワークに接続されているスポンサ経由とすることにより、スポンサがその情報PPにCIDを設定しCMを挿入すればよい。勿論、スポンサは、情報提供者PにCIDの設定およびCMの挿入を依頼することもできる。

【0210】

【第10実施形態】以下、本発明にかかる第10実施形態の課金システムを説明する。なお、第10実施形態において、第1実施形態と略同様の構成については、同一符号を付して、その詳細説明を省略する。

【0211】PID、TID、CIDに関する料金の設定を、情報PPの利用回数のような利用履歴に依存させることもできる。すなわち、利用回数が多いほど、情報PPの利用料金が安くなるなどの設定を、PID、TID、CIDに対して行えばよい。

【0212】図24は本実施形態における課金動作を説明する図である。図24において、Pは情報提供者、PP1（またはPPj）は情報提供者Pにより提供される情報、PID1（またはPIDj）は情報PP1に固有の情報固有データ、TID1（またはTIDj）は情報PP1に固有ではない付加データ、CID1（またはCIDj）はスポンサが設定したCM視聴に関するデータ、PPCは金銭情報、CHECKは情報PPの利用可否を判定する手段である。また、MMは情報PPの利用に関する履歴を記憶する記憶部である。利用履歴は、情報PPごとの利用回数とし、利用者以外には知られることはなく、利用者の情報PPの利用に関するプライバシーは保護される。

【0213】利用者はPPCの受け口1にPPCを挿入する。課金部のCHECKは、PPCから金銭情報を読み出すとともに、MMから情報PPの過去の利用回数を読み出し、読み出した利用回数に応じてPID+TID-CIDに示される料金よりPPCの残高が多く、PPCに利用料金を請求可能である場合に情報PPの利用を許可する。さらに、情報PPのPIDによる利用料金およびTIDによる利用料金が時間単位、あるいは、使用条件が変わる場合も、PPCに残高がある限りは、継続して情報PPを利用することができる。また、CMの再生（視聴）回数などによりCIDに記述された料金が、PPCに加算されるように構成することもできる。また、PPCは、他の実施形態で説明したように、現金、プリペイドカードなどの磁気カード、ICカードなどであり、

【0214】上記の例では、利用回数を利用履歴とする例を示したが、利用時間を利用履歴とする場合でも同じである。さらに、最終の利用結果を示す情報を利用履歴としてMMに格納すれば、長時間の映画などを分割して鑑賞することや、情報PPを分割して提供したり、何らかの障害により情報PPが途切れた場合などにも対応すること

ができる課金システムになる。この場合、PID、TID、CIDに情報の部分または時間ごとの料金を記述しておけば、図24と同様の構成により課金を実現できることは明らかである。

【0215】

【共通鍵暗号方式】共通鍵暗号方式は、送信者と受信者とは同一の暗号鍵を秘密に共有する暗号方式（秘密鍵暗号方式、対称暗号方式、慣用暗号方式とも呼ばれる）である。

【0216】共通鍵暗号方式は、適当な長さの文字列（ブロック）ごとに同じ鍵で暗号化するブロック暗号と、文字列またはビットごとに鍵を変えていくストリーム暗号とに分けることができる。ブロック暗号には、文字の順序を書換えて暗号化する転置式暗号や、文字を他の文字に換える換字式暗号などがある。この場合、転置や換字の対応表が暗号鍵になる。ストリーム暗号としては、多表を用いるビジュアル暗号や、一回限りの使い捨ての鍵を用いるパーナム暗号などが知られている。これらは、池野、小山著「現代暗号理論」（電子情報通信学会、1986）の第2章および第4章に詳しく説明されている。

【0217】また、ブロック暗号のなかでもアルゴリズムが公開されているDES(Data Encryption Standard)やFEAL(Past data Encipherment Algorithm)といった暗号が商用暗号として広く用いられている。これらは、辻井、笠原著「暗号と情報セキュリティ」（昭晃堂、1990）の第2章に詳しく説明されている。

【0218】ただし、DESやFEALはアルゴリズムを公開しているために暗号解読法も開発され、その解読法に対抗するために種々の変形が行われていることがある。例えば、後述する繰返し回数を増したり（C. H. Meyer and S. M. Matyas: "CRYPTOGRAPHY-A New Dimension in Computer Data Security", Wiley-Interscience, Appendix D, pp. 679-712, 1982）、鍵を頻繁に変える（山本、岩村、松本、今井: "2乗型擬似乱数生成器とブロック暗号を用いた実用的暗号方式", 信学技報, ISEC93-29, p. 65-75, 1993）などの変形が提案されている。

【0219】

【公開鍵暗号方式】公開鍵暗号方式は、暗号鍵と復号鍵とが異なり、暗号鍵を公開、復号鍵を秘密に保持する暗号方式である。従って、暗号鍵を公開鍵、復号鍵を秘密鍵と呼ぶこともある。

【0220】公開鍵暗号は共通鍵暗号にない次のような特徴をもつ。

【0221】(1)暗号鍵と復号鍵とが異なり、暗号鍵を公開することができるため、暗号鍵を秘密に配送する必要がなく、鍵の配送が容易である。

【0222】(2)各利用者の暗号鍵は公開されているので、利用者は各自の復号鍵のみ秘密に記憶しておけばよく、鍵の管理が容易である。

【0223】(3)送られてきた通信文の送信者が偽者でないこと、および、その通信文が改竄されていないことを、受信者が確認するための認証機能を実現できる。

【0224】公開鍵暗号の暗号通信と認証通信、および、認証機能付き暗号通信は、以下のようなプロトコルによって実現される。以下では、送信者Aから受信者Bへ暗号通信、認証通信、認証機能付き暗号通信を行う場合のプロトコルを示す。Aの秘密鍵をksA、公開鍵をkpAとし、Bの秘密鍵をksB、公開鍵をkpBとして、通信文Mに対して公開鍵kpを用いた暗号化操作をE(kp, M)とし、秘密の復号鍵ksを用いた復号操作をD(ks, M)と表す。

【0225】[暗号通信] AからBへ、通信文（平文）Mを秘密通信する場合は次の手順で行う。

【0226】ステップ1: Aは、Bの公開鍵kpBでMを暗号化し、暗号文CをBに送る。

$C = E(kpB, M)$

【0227】ステップ2: Bは、自分の秘密鍵ksBで暗号文Cを復号し、もとの平文Mを得る。

$M = D(ksB, C)$

【0228】受信者Bの公開鍵は、不特定多数に公開されているので、Aに限らずすべての人がBへ秘密の通信文を送ることができる。

【0229】[認証通信] AからBへ、通信文（平文）Mを認証通信する場合は次の手順で行う。

【0230】ステップ1: Aは、自分の秘密鍵ksAで通信文Sを生成しBに送る。

$S = D(ksA, M)$

【0231】ステップ2: Bは、Aの公開鍵kpAでSを復元変換し、元の平文Mを得る。

$M = E(kpA, S)$

【0232】もし、通信文Mが意味のある文であることが確認できれば、通信文Mが確かにAから送られてきたことが認証される。Aの公開鍵は、不特定多数に公開されているので、Bに限らずすべての人がAの署名文を認証できる。このような認証をデジタル署名ともいう。

【0233】[署名付暗号通信] AからBへ、通信文（平文）Mを署名付秘密通信する場合は次の手順で行う。

【0234】ステップ1: Aは、自分の秘密鍵ksAでMに署名し、署名文Sを作る。

$S = D(ksA, M)$

【0235】ステップ2: Aは、Bの公開鍵kpBで署名分Sを暗号化し、暗号文CをBに送る。

$C = E(kpB, S)$

【0236】ステップ3: Bは、自分の秘密鍵ksBでCを復号し、署名文Sを得る。

$S = D(ksB, C)$

【0237】ステップ4: Bは、Aの公開鍵kpAでSを復元変換し、元の平文Mを得る。

$M = E(kpA, S)$

【0238】もし、通信文Mが意味のある文であること

が確認できたならば、通信文が確かにAから送られてきたことが認証される。なお、ステップ1と2、ステップ3と4の順序はそれぞれ逆転してもよい。

【0239】代表的な公開鍵暗号方式の例を以下に挙げる。

【0240】暗号通信と認証通信ができる方式: RSA暗号(R. L. Rivest, A. Shamir and L. Adleman: "A method of obtaining digital signatures and public key cryptosystems", Comm. of ACM, 1978)、R暗号(M. Rabin: "Digitalized signatures and public-key cryptosystems", MIT/LCS/TR-212, Technical Report MIT, 1979)、W暗号(H. C. Williams: "A modification of the RSA public-key encryption procedure", IEEE Trans. Inf. Theory, 17-26, 6, 1980)、M暗号(松本、今井: "公開鍵暗号系の新しいアルゴリズム", 信学技報, 1782-84, 1982; T. Matsumoto and H. Imai: "A class of asymmetric cryptosystems based on polynomials over finite rings", IEEE International Symp. on Information Theory, 1983)

【0241】暗号通信のみができる方式: MD暗号(R. C. Merkle and M. E. Hellman: "Hiding information and signatures in trapdoor knapsacks", IEEE Trans. Inf. Theory, 17-24, 5, 1978)、GS暗号(A. Shamir and R. E. Zippel: "On the security of the Merkle-Hellman cryptographic scheme", IEEE Trans. Inf. Theory, 17-28, 3, 1980)、CR暗号(B. Chor and R. L. Rivest: "A knapsack type public key cryptosystem based on arithmetic infinite field", Proc. Crypto84)、MR暗号(R. J. McEliece: "A public-key cryptosystem based on algebraic coding theory", DSN Progress Rep., Jet Propulsion Lab., 1978)、E暗号(T. E. ElGamal: "A public key cryptosystem and a signature scheme based on discrete logarithm", Proc. Crypto 84, 1984)、T暗号(辻井重男: "行列分解を利用した公開鍵暗号の方式", 信学技報, 1785-12, 1985)

【0242】認証通信のみができる方式: S暗号(A. Shamir: "A fast signature scheme", Report MIT/LCS/TM-107, MIT laboratory for computer science, Cambridge, Mass., 1978)、L暗号(K. Lieberherr: "Uniform complexity and digital signature", Lecture Notes in Computer Science 115 Automata, Language and Programming, Eighth Colloquium Acre, Israel, 1981)、GVN暗号(S. Goldwasser, S. Micali and A. Yao: "Strong signature schemes", ACM Symp. on Theory of Computing, 1983)、GM暗号(S. Goldwasser, S. Micali and R. L. Rivest: "A 'paradoxical' solution to the signature problem", ACM Symp. on Foundation of Computer Science, 1984)、OSS暗号(H. Ong, C. P. Schnorr and A. Shamir: "An efficient signature scheme based on quadratic equation", ACM Symp. on Theory of Computing,

1984)、OS暗号(岡本、白石: "多項式演算によるデジタル署名方式", 信学論(D), J68-D, 5, 1985; T. Okamoto and A. Shirai: "A fast signature scheme based on quadratic inequalities", IEEE Symp. on Theory of Computing, 1984)

【0243】

【他の実施形態】本発明の目的は、前述した実施形態の機能を実現するソフトウェアのプログラムコードを記録した記憶媒体を、システムあるいは装置に供給し、そのシステムあるいは装置のコンピュータ(またはCPUやMPU)が記憶媒体に格納されたプログラムコードを読出し実行することによっても、達成されることは言うまでもない。この場合、記憶媒体から読出されたプログラムコード自体が前述した実施形態の機能を実現することになり、そのプログラムコードを記憶した記憶媒体は本発明を構成することになる。プログラムコードを供給するための記憶媒体としては、例えば、フロッピーディスク、ハードディスク、光ディスク、光磁気ディスク、CD-ROM、CD-R、磁気テープ、不揮発性のメモリアカード、ROMなどを用いることができる。

【0244】また、コンピュータが読出したプログラムコードを実行することにより、前述した実施形態の機能が実現されるだけでなく、そのプログラムコードの指示に基づき、コンピュータ上で稼働しているOS(オペレーティングシステム)などが実際の処理の一部または全部を行い、その処理によって前述した実施形態の機能が実現される場合も含まれることは言うまでもない。

【0245】さらに、記憶媒体から読出されたプログラムコードが、コンピュータに挿入された機能拡張カードやコンピュータに接続された機能拡張ユニットに備わるメモリに書込まれた後、そのプログラムコードの指示に基づき、その機能拡張カードや機能拡張ユニットに備わるCPUなどが実際の処理の一部または全部を行い、その処理によって前述した実施形態の機能が実現される場合も含まれることは言うまでもない。

【0246】このように、本発明にかかる各実施形態によれば、前述した課題(1)から(5)を解決する課金方式および課金システムを実現することができる。

【0247】すなわち、利用者は種々の情報をレンタル的に安価に利用し、利用者のプライバシーも保護され、情報提供者は利用者ごとの情報利用の管理を行うことなく、情報の利用に応じて利用料金の分配を受けることができる。

【0248】また、販売店を含む料金分配者や料金立替者を導入することにより、料金の支払いまでを含めて使い勝手のよい課金システムを構成することができる。

【0249】また、情報に固有でない付属データにより、情報提供者以外の、ネットワークに関する種々の提供者にも正当な料金を分配することができる柔軟な課金システムを構築することができる。

【0250】また、利用者以外にも、スポンサが料金を負担することができる、種々の用途に対応する課金システムを実現することもできる。

【0251】さらに、時間や使用条件の段階に応じて情報の利用可否を判定したり、課金条件を変えるなどが可能であり、きめ細かな課金システムを実現することができる。

【0252】

【発明の効果】以上説明したように、本発明によれば、利用申し込み手続や、多数の利用者固有データの管理が不要な課金システムおよびその方法を提供することができる。

【0253】また、利用者のプライバシーを保護する課金システムおよびその方法を提供することができる。

【0254】また、料金の請求および徴収が容易な課金システムおよびその方法を提供することができる。

【0255】また、提供情報だけでなく伝送路や端末の提供に対する課金も行う課金システムおよびその方法を提供することができる。

【0256】また、提供情報の利用の段階に応じて利用可否を判定し、その判定結果に応じて情報の利用を制限し、課金を行う課金システムおよびその方法を提供することができる。

【図面の簡単な説明】

【図1】超流通の概念図、

【図2】第1実施形態の課金方式を示す図、

【図3】第2実施形態の課金方式を示す図、

【図4】第3実施形態の課金方式を示す図、

【図5】第3実施形態におけるネットワークを示す図、

【図6】第4実施形態の課金方式を示す図、

【図7】第4実施形態におけるネットワークを示す図、

【図8】第5実施形態の課金方式を示す図、

* 【図9】第6実施形態の課金方式を示す図、

【図10】第6実施形態におけるネットワークを示す図、

【図11】第8実施形態におけるネットワークを示す図、

【図12】第8実施形態のマルチメディアネットワークに関するすべての提供者へ情報単位で料金を分配する課金方式を示す図、

【図13】階層符号データの一般的な概念を示す図、

【図14】画像圧縮に関する課金の実施例1における課金動作を説明する図、

【図15】MP3GにおけるI,P,B-ピクチャの組み合わせを示す図、

【図16】画像圧縮に関する課金の実施例2における課金動作を説明する図、

【図17】暗号技術の課金に関する実施例における課金動作を説明する図、

【図18】暗号の種類に応じた課金の実施例における課金動作を説明する図、

【図19】画像品位に対する課金の実施例における課金動作を説明する図、

【図20】第8実施形態における第二の課金方式を示す図、

【図21】第8実施形態における第三の課金方式を示す図、


【図22】第9実施形態におけるネットワークを示す図、

【図23】第9実施形態における課金動作を説明する図、


【図24】第10実施形態における課金動作を説明する図である。

*


【図1】




【図2】




【図 4】




【圖 6】




【圖8】




【図9】




【図11】




【図12】




【図13】




【図15】




【図16】




【図14】




【図17】




【図18】




【図19】




【図20】




【図21】



【図22】



【図23】



【図24】

